

# **Groves** *INDUSTRIAL*

*a DGI Supply Company*



# PISTOL GRIP IMPACTS



## MP-2315-HE

1/2" IMPACT WRENCH

Square Drive	1/2"
Max Torque	680 ft-lbs
Free Speed	8000 rpm

Length	7-1/4"
Weight	5.8 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	4.2 cfm



## MP-2144QR

1/2" IMPACT WRENCH

Square Drive	1/2"
Max Torque	900 ft-lbs
Free Speed	8000 rpm

Length	7-3/4"
Weight	5.0 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	6.7 cfm



## MP-2146QR

3/4" IMPACT WRENCH

Square Drive	3/4"
Max Torque	1300 ft-lbs
Free Speed	6000 rpm

Length	8-11/16"
Weight	8.20 lbs
Air Inlet	3/8"
Rec'd Hose	1/2"
Avg. Air Cons.	7.3 cfm



## MP-2148QR

1" IMPACT WRENCH

Square Drive	1"
Max Torque	1400 ft-lbs
Free Speed	6000 rpm

Length	8-7/8"
Weight	8.42 lbs
Air Inlet	3/8"
Rec'd Hose	1/2"
Avg. Air Cons.	7.3 cfm

# PISTOL GRIP IMPACTS



## MP-2660

3/4" IMPACT WRENCH

Square Drive	3/4"
Max Torque	1100 ft-lbs
Free Speed	5500 rpm

Length	9"
Weight	9.50 lbs
Air Inlet	3/8"
Rec'd Hose	1/2"
Avg. Air Cons.	14-38 cfm

6" Extended Anvil Also Available\*



750SS



751SS



754SS

Model	Drive	Max Torque (F)	Max Torque (R)	Free Speed	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
750SS	3/4"	1800 ft-lbs	2000 ft-lbs	4600 rpm	9"	13.5 lbs	3/8"	1/2"	58 cfm
751SS	1"	1800 ft-lbs	2000 ft-lbs	4600 rpm	9"	13.5 lbs	3/8"	1/2"	58 cfm
754SS	#4 Spline	1800 ft-lbs	2000 ft-lbs	4600 rpm	9"	13.5 lbs	3/8"	1/2"	58 cfm

# HEAVY-DUTY IMPACTS

## MP-2740-ST

1" IMPACT WRENCH



Square Drive	1"
Max Torque	2500 ft-lbs
Free Speed	5000 rpm

Length	16-3/16"
Weight	22 lbs
Air Inlet	1/2"
Rec'd Hose	1/2"
Avg. Air Cons.	10 cfm

6" Extended Anvil Also Available\*

## MP-2940B2

1" IMPACT WRENCH



Square Drive	1"
Max Torque	1600-2000 ft-lbs
Free Speed	5000 rpm

Length	12-13/32"
Weight	22 lbs
Air Inlet	1/2"
Rec'd Hose	3/4"
Avg. Air Cons.	58 cfm

#5 Spline Also Available\*

## MP-2950B7

1-1/2" IMPACT WRENCH



Square Drive	1-1/2"
Max Torque	2500-3000 ft-lbs
Free Speed	3750 rpm

Length	14-1/2"
Weight	33 lbs
Air Inlet	1/2"
Rec'd Hose	3/4"
Avg. Air Cons.	70 cfm

#5 Spline Also Available\*

## MP-5980

1-1/2" IMPACT WRENCH



Square Drive	1-1/2"
Max Torque	10,000 ft-lbs
Free Speed	830 rpm

Length	23"
Weight	88 lbs
Air Inlet	3/4"
Rec'd Hose	1"
Avg. Air Cons.	138 cfm

2-1/2" & 3-1/2" Models Also Available\*

# ACCESSORIES

## PORTABLE AIR LINE LUBRICATORS

Designed to supply oil to air tools where it is not practical to use stationary lubricators. Can be installed as far away as 25 feet. Oil flows into the line each time the tool is started. Easy and inexpensive way to keep air tools operating at peak efficiency. Features adjustable oil flow, visible oil supply and rugged casting for use in severe conditions.

MP-02000PR      PRESSURE RELIEF CAP  
MPLRK              REPAIR KIT



0-R  
SHOWN WITH OPTIONAL PRESSURE RELEASE CAP

Model	Oil Capacity	Pipe Size	Rec'd Air Flow @90 PSI	Max. PSI	Length	Height	Weight
0-R	1.4 oz	1/2"	30 cfm	500	4-1/2"	2-1/4"	0.88 lbs
1-R	3.7 oz	3/4"	70 cfm	260	6"	2-3/4"	1.50 lbs
2-R	11.0 oz	3/4"	70 cfm	300	7"	3-1/2"	2.00 lbs
2A-R	11.0 oz	1"	70 cfm	300	7"	3-1/2"	2.00 lbs
3-R	16.0 oz	1"	150 cfm	250	10"	3-3/4"	4.25 lbs

## IN-LINE LUBRICATOR W/ INTEGRATED FILTER



1L-F

Model	Oil Capacity	Pipe Size	Rec'd Air Flow @90 PSI	Max. PSI	Height
0L-F	1.4 oz	1/2"	30 cfm	500	2-1/4"
1L-F	3.7 oz	3/4"	70 cfm	260	2-3/4"

## SAFETY LOCK CABLES

Helps prevent injury due to broken hose connections. Spring-powered loops provide a firm grip on the hose. Bleed air pressure from hose before removing safety lock cable.



SLC1

Model	Cable Description (Dia. x L)	Fits Hose OD
SLC1	1/8" x 20"	1/2" to 1-1/4"
SLC2	1/4" x 38"	1-1/2" to 3"

## LUBRICATOR WHIP HOSE ASSEMBLIES



MP-3HW-HDS



MP-4HW-HDS



WH-755-2R

Model	Assembly Components		
	Fitting to Tool	Hose	Lubricator
MP-1HW-HDS	1/4" MPT	1/2" ID x 6 ft	0-R
MP-2HW-HDS	3/8" MPT		
MP-3HW-HDS	1/2" MPT		
MP-4HW-HDS	L-1-E Swivel (7/8"-24 thread)	3/4" ID x 5 ft	2-R
MP-4HW-0.500-HDS	L-3-E Swivel (1/2" MPT)		
WH-755-2R	3/4" Universal Coupling		

## HYDRAULIC WHIP HOSE ASSEMBLIES



3HW-HYD



3HW-HYD-F

Model	Assembly Components			
	Fitting to Tool	Hose	Lubricator	Filter
2HW-HYD	3/8" MPT	1/2" ID x 6 ft	0-R w/CP Fitting	-
3HW-HYD	1/2" MPT			
3HW-HYD-F	1/2" MPT			9074M

# DIE GRINDERS

## MP-2753-ST

1/4" DIE GRINDER [REAR EXHAUST]



Collet Size	1/4"
Max HP	0.30 hp
Free Speed	25,000 rpm

Length	6-1/4"
Weight	0.9 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	4 cfm

## MP-2754-ST

1/4" EXTENDED DIE GRINDER [REAR EXHAUST]



Collet Size	1/4"
Max HP	0.30 hp
Free Speed	25,000 rpm

Length	10"
Weight	0.9 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	4 cfm

## MP-SM542

1/4" ANGLE DIE GRINDER [SIDE EXHAUST]



Collet Size	1/4"
Max HP	0.30 hp
Free Speed	20,000 rpm
Height	2-27/32"

Length	5-3/16"
Weight	1.1 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	4 cfm

## MP-7252-ST

1/4" ANGLE DIE GRINDER [REAR EXHAUST]



Collet Size	1/4"
Max HP	0.30 hp
Free Speed	20,000 rpm
Height	3"

Length	6-1/2"
Weight	1.1 lbs
Air Inlet	1/4"
Rec'd Hose	3/8"
Avg. Air Cons.	4 cfm

# CLASSIC SERIES GRINDERS



MP-9113-14



MP-9113A-38



MP-9113E-14

Model	Collet Size	Free Speed	Max HP	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
MP-9113-14	1/4"	25,000 rpm	1 hp	6-1/4"	2.25 lbs	1/4"	3/8"	11.9 cfm
MP-9113A-38	3/8"	25,000 rpm	1 hp	6-1/4"	1.50 lbs	1/4"	3/8"	11.9 cfm
MP-9113E-14	1/4"	25,000 rpm	1 hp	11-1/16"	3.30 lbs	1/4"	3/8"	11.9 cfm



MP-3040-C



MP-3040E-C



MP-3040



MP-3040-E4

Model	Collet Size	Wheel Size	Spindle Thread	Free Speed	Max HP	Height	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
MP-3040-C	1/4"	—	—	13,500 rpm	1 hp	2-1/2"	8"	2.75 lbs	1/4"	3/8"	10 cfm
MP-3040E-C	1/4"	—	—	13,500 rpm	1 hp	2-1/2"	10"	3.20 lbs	1/4"	3/8"	10 cfm
MP-3040	—	4"	3/8"-24	13,500 rpm	1 hp	2-1/2"	8"	3.125 lbs	1/4"	3/8"	26 cfm
MP-3040-E4	—	4"	3/8"-24	13,500 rpm	1 hp	2-1/2"	10"	3.5 lbs	1/4"	3/8"	26 cfm

# 9500 SERIES GRINDERS

**WOW!**

**NEW TOOL**

## MP-9516EXTASR-14F2

1/4" LOW PROFILE GRINDER



Capacity	1/4" Female Thread	Length	9-5/8"
Max HP	0.95 hp	Weight	3.3 lbs
Free Speed	16,500 rpm	Air Inlet	1/4"
Height	1-3/8"	Rec'd Hose	3/8"
		Avg. Air Cons.	18-20 cfm



ANGLE



ROUTERS



EXTENDED ANGLE



STRAIGHT



EXTENDED STRAIGHT

# 9500 SERIES GRINDERS



Michigan Pneumatic Tool is proud to present the 9500 Series of grinders. Our new family of grinders is designed to meet the most demanding requirements of all industrial applications.

- Designed with the operator in mind to be small, comfortable and lightweight.
- Robust .95 horse power motor provides the power needed for a high rate of material removal.
- All metal construction of quality, precision components achieves maximum durability and performance.
- Parts interchangeability between all MP-9500 Series tools results in easier and more affordable maintenance.
- Use the charts below to determine the specific model number of the tool you require.

## Model Number Identification Chart

MP-95	XX	XXXXX	X	—	XX	XXX
Series	RPM	Description	Exhaust		Termination	Capacity
Michigan Pneumatic 9500 Series	<b>11</b>	11,500 rpm	<b>DG</b> Straight Die Grinder	<b>F</b> Front		Collets 1" Carbide Burr, 2" Wheel
	<b>13</b>	13,500 rpm	<b>WG</b> Straight Wheel Grinder	<b>R</b> Rear	<b>C4</b> 1/4" Collet	<b>3CW</b> 1.25" Cone Wheel
	<b>16</b>	16,500 rpm	<b>EXTDG</b> Extended Die Grinder	<b>S</b> Side	<b>C6</b> 3/16" Collet	<b>4T1</b> 4" Guard Type 1 Wheel
	<b>18</b>	18,000 rpm	<b>EXTHG</b> Extended Horizontal Grinder		<b>C6M</b> 6mm Collet	<b>4T7</b> 4" Guard Type 27 Wheel
	<b>20</b>	20,000 rpm	<b>AG</b> Angle Grinder		<b>C3</b> 3/8" Collet	<b>5T1</b> 5" Guard Type 1 Wheel
	<b>24</b>	24,000 rpm	<b>EXTAG</b> Extended Angle Grinder		<b>C5</b> 5/16" Collet	<b>5T7</b> 5" Guard Type 27 Wheel
	<b>25</b>	25,000 rpm	<b>RT</b> Router		<b>C8</b> 1/8" Collet	
					<i>External Thread</i>	
					<b>38</b> 3/8"-24	
					<b>12</b> 1/2"-13	
				<b>58</b> 5/8"-11		

## Specification Chart

Configuration	Exhaust Options	Termination Options	Capacity Options	Motor Speed Options	Max HP	Height	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
Router	Front	1/4" Collet, 3/8" Collet	—	18,000 rpm, 25,000 rpm	0.95	—	8"	2.45 lbs	1/4"	3/8"	30 cfm
Straight	Front, Rear, Side	1/4" Collet, 3/16" Collet, 6mm Collet, 3/8" Collet, 5/16" Collet, 1/8" Collet, 3/8"-24 External Thread	1" Carbide Burr, 2" Wheel, 4" Guard w/Type 1 Wheel	18,000 rpm, 20,000 rpm, 24,000 rpm, 25,000 rpm	0.95	—	6.9" (7.4" Rear Exhaust)	1.9 lbs	1/4"	3/8"	30-35 cfm
Angle	Front, Rear, Side	1/4" Collet, 3/16" Collet, 6mm Collet, 3/8" Collet, 5/16" Collet, 1/8" Collet, 3/8"-24 External Thread, 5/8"-11 External Thread	1" Carbide Burr, 2" Wheel, 4" Guard/Type 1 Wheel, 4" Guard/Type 27 Wheel, 5" Guard/Type 1 Wheel, 5" Guard/Type 27 Wheel	11,500 rpm	0.95	3.25"	7.6" (8.3" Rear Exhaust)	3-3.9 lbs	1/4"	3/8"	30-35 cfm
Extended Angle	Front, Rear, Side	1/4" Collet, 3/16" Collet, 6mm Collet, 3/8" Collet, 5/16" Collet, 1/8" Collet, 3/8"-24 External Thread	1" Carbide Burr, 2" Wheel, 4" Guard/Type 1 Wheel, 4" Guard/Type 27 Wheel	13,500 rpm, 16,500 rpm	0.95	2.3"	9.6" (10.1" Rear Exhaust)	3.3 lbs	1/4"	3/8"	30-35 cfm
Extended Straight	Rear, Side	1/4" Collet, 3/16" Collet, 6mm Collet, 3/8" Collet, 5/16" Collet, 1/8" Collet, 3/8"-24 External Thread, 1/2"-13 External Thread	1" Carbide Burr, 2" Wheel, 1.25" Cone Wheel, 4" Guard/Type 1 Wheel	18,000 rpm, 20,000 rpm, 24,000 rpm, 25,000 rpm	0.95	—	12.3" (12.8" Rear Exhaust)	2.3 lbs	1/4"	3/8"	30-35 cfm

# PROFESSIONAL SERIES



WWW.SIEMENS.COM/PRESS



G25300



G25304B



G25306B



G25308B

## Replacement Parts

#25300-27	Collet
#25300-29	Collet Nut
#25300-28	Nose Piece
#25300-30	Wrench
#25300-31	Wrench

	G25300	G25304B	G25306B	G25308B
Collet Size	1/4"	1/4"	1/4"	1/4"
Maximum HP	0.30 hp	0.30 hp	0.30 hp	0.30 hp
Free Speed	25,000 rpm	25,000 rpm	25,000 rpm	25,000 rpm
Height	1-5/16"	1-5/16"	1-5/16"	1-5/16"
Extension Length	–	3-1/2"	5-1/2"	7-1/2"
Overall Length	5-5/8"	9-1/8"	11-1/8"	13-1/8"
Weight	0.82 lbs	1.30 lbs	1.50 lbs	1.70 lbs
Air Inlet Thread	1/4"	1/4"	1/4"	1/4"
Rec'd Hose Size	1/4"	1/4"	1/4"	1/4"
Avg. Air Consumption	10 cfm	10 cfm	10 cfm	10 cfm

# PROFESSIONAL SERIES



G18901F



G22601F



G12390



G20390



G12390-BA

## Replacement Parts

#0390-33	Collet
#0390-35	Collet Nut
#0390-34	Nose Piece
#0390-36	Wrench
#0390-37	Wrench



	G18901F	G22601F	G12390-BA	G20390-BA	G12390	G20390
Capacity	1/4" Collet	1/4" Collet	1/2" x 12" Belt	1/2" x 12" Belt	1/4" Collet	1/4" Collet
Maximum HP	0.90 hp	0.60 hp	0.30 hp	0.30 hp	0.30 hp	0.30 hp
Free Speed	18,000 rpm	22,000 rpm	12,000 rpm	20,000 rpm	12,000 rpm	20,000 rpm
Height	—	—	—	—	2-13/16"	2-13/16"
Length	6-1/2"	5-3/4"	10-3/8"	10-3/8"	5-3/4"	5-3/4"
Weight	1.43 lbs	1.28 lbs	1.50 lbs	1.50 lbs	1.12 lbs	1.12 lbs
Air Inlet Thread	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Rec'd Hose Size	3/8"	3/8"	1/4"	1/4"	1/4"	1/4"
Avg. Air Consumption	27 cfm	21 cfm	8 cfm	10 cfm	8 cfm	10 cfm

# ANGLE GRINDERS



## MP-1954PS-ST

5" ANGLE GRINDER

Wheel Size	4-1/2"	Length	9-13/32"
Spindle Thread	5/8"-11	Weight	4.4 lbs
Max HP	0.90 hp	Air Inlet	1/4"
Free Speed	12,000 rpm	Rec'd Hose	3/8"
Height	3-3/4"	Avg. Air Cons.	4 cfm



MP-250L-ST

MP-250L-ST58

## MP-250L-ST MP-250L-ST58

ANGLE GRINDER

Model	Wheel Size	Spindle Thread	Free Speed	Max HP	Height	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
MP-250L-ST	4" Type 27	3/8"-24	12,000 rpm	1 hp	3-1/4"	9"	4.5 lbs	1/4"	3/8"	23 cfm
MP-250L-ST58	5"	5/8"-11	12,000 rpm	1 hp	3-1/4"	9"	4.5 lbs	1/4"	3/8"	23 cfm



## MP-2312-585T7

ANGLE GRINDER

Wheel Size	5"	Length	10"
Spindle Thread	5/8"-11	Weight	4.5 lbs
Max HP	2.3 hp	Air Inlet	3/8"
Free Speed	12,000 rpm	Rec'd Hose	1/2"
Height	3.43"	Avg. Air Cons.	35 cfm

# HORIZONTAL GRINDERS



MP-1514SG-384T1



MP-1514DGF-C4



MP-1512SG-383CW



MP-1518SG-BGA21

Model	Collet Size	Wheel Size	Spindle Thread	Free Speed	Max HP	Length	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
MP-1514DGF-C4*	1/4"	—	—	12,000 rpm	1.5 hp	8-5/8"	2.75 lbs	3/8"	3/8"	19-21 cfm
MP-1512SG-383CW	—	1.25" Cone	3/8"-24	12,000 rpm	1.5 hp	14-3/8"	3.5 lbs	1/4"	3/8"	19-21 cfm
MP-1514SG-384T1	—	4" Type 1	3/8"-24	14,000 rpm	1.5 hp	14-3/8"	3.5 lbs	1/4"	3/8"	19-21 cfm
MP-1518SG-BGA21	Special 12" x 1" Belt Sander Gear Head			18,000 rpm	1.5 hp	14-3/8"	3.5 lbs	1/4"	3/8"	19-21 cfm

\*Available in 9000, 12,000, 14,000 and 18,000 rpm. Available with 1/4", 3/8" or 6mm collets. Side exhaust option available as well.



**MP-2511**  
5/8"-11 CONE WHEEL GRINDER

Wheel Size	Cone	Length	18"
Spindle Thread	5/8"-11	Weight	6.75 lbs
Max HP	1.5 hp	Air Inlet	1/2"
Free Speed	12,000 rpm	Rec'd Hose	3/8"
		Avg. Air Cons.	32 cfm

# VERTICAL GRINDERS



MP-5666VSC-ORANGE



MP-6666VSC-ORANGE



MP-5667VS-ORANGE



MP-6667VS-ORANGE



MP-5669VS-ORANGE



MP-6669VS-ORANGE

Model	Wheel Size	Spindle Thread	Free Speed	Max HP	Height	Weight	Air Inlet Thread	Rec'd Hose Size	Avg. Air Cons.
MP-5666VSC-ORANGE	6" Cup	5/8"-11	6000 rpm	3 hp	7-5/8"	10.2 lbs	1/2"	1/2"	45 cfm
MP-5667VS-ORANGE	7"	5/8"-11	6000 rpm	3 hp	7-5/8"	9.4 lbs	1/2"	1/2"	45 cfm
MP-5669VS-ORANGE	9"	5/8"-11	6000 rpm	3 hp	7-5/8"	9.85 lbs	1/2"	1/2"	45 cfm
MP-6666VSC-ORANGE	6" Cup	5/8"-11	6000 rpm	4 hp	7-5/8"	11.6 lbs	1/2"	1/2"	40 cfm
MP-6667VS-ORANGE	7"	5/8"-11	6000 rpm	4 hp	7-5/8"	10.7 lbs	1/2"	1/2"	45 cfm
MP-6669VS-ORANGE	9"	5/8"-11	6000 rpm	4 hp	7-5/8"	11.2 lbs	1/2"	1/2"	45 cfm

# SERVICE & REPAIR


## WHAT WE DO

Michigan Pneumatic Tool is a full service air tool company celebrating 70 years as a leader in the design, distribution, manufacture, repair and rebuilding of industrial air tools. At MPT we service construction, industrial, demolition, bolting and foundry tools. Our service department is staffed by experienced technicians that are trained to rebuild any industrial grade air tool. We take pride in the ability to service virtually any make or model whether it is current or discontinued.

## HOW WE DO IT

Send your tool to MPT and experience the best service in the industry:

- ◆ An estimate is provided for repair within 3 business days of receiving your tool(s).
- ◆ Every tool is completely disassembled, cleaned and examined for wear and tear during the estimate process.
- ◆ Worn or damaged parts are replaced to reduce future maintenance costs or unnecessary tool replacement.
- ◆ Every tool is tested by our technicians then painted before it is returned to you.
- ◆ Note: When the cost to repair exceeds 50% of the cost of the tool, we will quote you a replacement tool as an option during the estimate process.
- ◆ Our tool repairs are completely guaranteed.
- ◆ To better serve our customers in the Gulf Coast, we even have an authorized repair center in Houston, TX for your convenience.



**Groves INDUSTRIAL**  
a DGI Supply Company

In Proud Partnership with



**MICHIGAN  
PNEUMATIC TOOL**



**MICHIGAN PNEUMATIC TOOL**  
SUPPORTS YOUR BUSINESS WITH A WIDE  
SELECTION OF NEW AND REBUILT TOOLS IN  
STOCK AND AN UNRIVALED PARTS INVENTORY  
THAT INCLUDES BRAND NAME, HARD TO  
FIND, OBSOLETE AND DISCONTINUED PARTS.

7301 Pinemont Dr. Houston, TX 77040 • [www.grovesindustrial.com](http://www.grovesindustrial.com) • 713.675.4747 FAX: 731.675.6924

HAND TOOLS • POWER TOOLS • ABRASIVES • CUTTING TOOLS • MACHINE & PRECISION TOOLS • PAINT & CHEMICALS • HEALTH & SAFETY • MRO SUPPLIES  
MATERIAL HANDLING • JANITORIAL SUPPLIES • INTEGRATED SOLUTIONS • BAND SAWS & BLADES