

MATERIAL SAFETY DATA SHEET APEX 9500 WATER SOLUBLE CUTTING OIL

I. PRODUCT AND MANUFACTURER INFORMATION		
Product name	APEX 9500 WATER SOLUBLE CUTTING OIL	
Chemical name	PETROLEUM OIL	
Synonyms	SOLUBLE CUTTING OIL	
CAS number	NE	
Manufacturer	Ashburn Chemical Technologies	
	7403 Wright Rd	
	Houston, TX 77041	
Emergency phone number	USA: 800-424-9300 (CHEMTREC)	
	Outside USA: 703-527-3887 (CHEMTREC)	
General Information	832-399-1000	
Date of last revision	10/11/11	

II. HAZARDOUS INGREDIENT	S				
HAZARDOUS COMPONENT	CAS NUMBER	% Optional	OSHA PEL	ACGIH TLV	CHEMICAL AND/OR COMMON NAME(S)
Severely hydro-treated light naphthenic distillate	64742-53-6		5mg/m3	5mg/m3	Petroleum Oil

III. PHYSICAL AND CHEMICAL CHARACTERISTICS		
Boiling point @ 760 mm Hg	N/D	
Vapor pressure at 20 °C	N/D	
Vapor density (air $= 1$)	N/D	
Solubility in water	Complete, Forms Emulsion	
Appearance and odor	Blue Green Transparent Liquid	
Specific gravity ($H_2O = 1.0$)	0.93	
pH of solution @ 10:1	9.4	
Melting point	N/D	
Evaporation rate (butyl acetate $= 1$)	<1	

IV. FIRE AND EXPLOSION HAZARD DATA			
Combustible/Not combustible	Not combustible		
Flammable/Not flammable	Not flammable		
Pyrophoric/Not pyrophoric	Not pyrophoric		
Explosive/Not explosive	Not explosive		
Flash point (test method)			
	300F PMCC		
Flammable limits (in Air % by volume)	N/D		
Extinguishing media	Water spray, foam or carbon dioxide		
Special fire-fighting procedures or equipment	Intense heat can cause drums to rupture.		
	Cool fire-exposed containers with water. Treat as hot oil. Fire		
	Fighters should wear NIOSH approved self-contained		
	breathing apparatus.		
Unusual fire and explosion hazards	Intense heat can cause drums to rupture.		
	Cool fire-exposed containers with water.		

V. REACTIVITY DATA	
Material is stable/unstable	Stable
Conditions to avoid	Strong oxidizers
Incompatibility (materials to avoid)	Strong oxidizers
Hazardous decomposition under fire conditions	Fumes, smoke, carbon monoxide, aldehydes and other



	decomposition by-products, in the case of incomplete
	combustion
Hazardous polymerization will/will not occur	Will not occur

VI. HEALTH HAZARD DATA

Threshold limit value	TLV for this product not established. Refer to the hazardous materials list for TLV of individual ingredients.	
Primary route(s) of entry	Inhalation, Ingestion	
Known Hazards Under 29 CFR 1910.1200		
Mutagenic (genetic defects)	None	
Reproductive	None	
Systemic	None	
Teratogenic (birth defects)	None	
Carcinogen listed in:		
NTP (National Toxicology Program)	NO	
IARC Monographs	NO	
OSHA	NO	
Signs and symptoms of exposure		
Inhalation	If TLV is exceeded, inhalation of oil mist is harmful and may	
	cause lung damage.	
Skin contact	No irritation under normal conditions.	
Eye contact	Contact may cause irritation	
Ingestion	May cause nausea	
Emergency first aid procedures		
Inhalation	Remove to fresh air. If symptoms persist, consult a physician.	
Skin contact	Wash off with soap and water	
Eye contact	Flush with large amounts of water.	
Ingestion	Do not induce vomiting. Do not administer liquids. Obtain	
-	medical assistance.	
Medical conditions generally aggravated by exposure		
Notes to physician	Treatment of overexposure should be directed toward the	
	control of symptoms and the clinical condition.	

VII. PRECAUTIONS FOR SAFE HANDLING	AND USE
Steps to take if released or spilled	Treat as an oil spill. Dike area. Clean up with adsorbents. Do not flush into drain or sewers. Place in a DOT approved container for disposal.
Waste disposal method	According to federal, state and local regulations.
Precautions for handling and storing	Launder contaminated clothing before reuse. Avoid prolonged breathing of mist and vapors. Use as directed. Store away from food. Keep containers closed when not in use. Avoid prolonged and repeated skin contact with concentrate and all contact with eyes. Wash thoroughly after handling. Do not ingest.
Other precautions	
Hazard ratings	HMIS
Health	1
Flammability	1
Reactivity	0
Personal protection	В



VIII. CONTROL MEASURES

Protective gloves (type and material)	Oil resistant gloves for prolonged or repeated contact.
Eye protection	Safety glasses or goggles.
Other protective clothing or equipment	
Respiratory protection (specify type)	None normally required. If TLV is exceeded, use NIOSH approved respirator.
Ventilation and conditions	
Local	Local exhaust ventilation may be necessary if misting is generated.
Mechanical	
Other	
Special	
Work/hygienic practices	Launder contaminated clothing before reuse. Avoid prolonged breathing of mist and vapors. Use as directed. Normal precautions common to good manufacturing should be followed in handling and storing. Store away from food. Wash hands before eating, drinking, or smoking.

IX. ADDITIONAL REGULATORY INFORMATION		
SARA hazard category (Section 311 and 312 of the	Delayed (Chronic) Health Hazard	
Superfund Amendment and Reauthorization Act of		
1986 (SARA Title III)		
Toxic chemical(s) subject to the supplier notification requirements of section 313 of the Superfund	None	
Amendment and Reauthorization Act of 1986 (SARA)		
and the requirements of 40 CFR part 372		
Ingredient(s) regulated under the Clean Air Act Section	None	
112 hazardous air pollutants and subject to all reporting		
requirements of CERCLA (Superfund)		

NA – not applicable NR – not reported ND – not determined NE – not established UN – unknown

The information presented in this MSDS has been compiled from sources deemed reliable. This MSDS is presented in good faith and believed to be accurate as of the effective date shown above. No warranty, expressed or implied, is given. Regulatory requirements are subject to change and may differ from one location to another. It is the responsibility of the buyer to insure compliance with federal, state, provincial and local laws and regulations.