

Cotton knit PVC coating

DESCRIPTION

- Fully coated, extra coating over entire hand
- · Scalloped edge
- · Rough finish over entire surface
- · Antibacterial and anti-odour treatment
- · Anatomical shape
- Seamless knit



RECOMMENDED FOR THESE RISKS:

Cold

Chemicals

Abrasion

Micro-cuts

RECOMMENDED FOR THESE LINES OF WORK:

Chemical industry / Alkaline components

Chemical industry / Acid components

Construction / Painting

Construction / Public works

Fishing and agriculture

BENEFITS

- A flexible, soft glove that absorbs perspiration, for ultra comfortable extended wear and with good mechanical resistance.
- Seals and protects the hand against chemicals while remaining flexible
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- · Surface provides tactile feel and better grip
- · Greater hygiene
- · Designed for easy movement and continuous wear
- · No irritation by seams in contact with the skin
- · Wrist well protected

AVAILABLE SIZES	7/S • 8/M • 9/L • 10/XL • 11/XXL
LENGTH Dependent on size, in mm (flat)	300-320
PACKAGING Pairs per pack/box	10/120
COLOUR OF SUPPORT/COATING	Orange
THICKNESS in mm	1.10

RECOMMENDATIONS FOR USE

- The size given corresponds to a well fitting glove
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work – other factors may influence the performance.
- Do not use with chemicals other than those tested without prior trials

<u>X</u> 1 2 3 4 5 6

N-HEPTANE

· Store away from light and humidity

EN 374-3 - 2003

ABRASION CUTTING 0 1 2 3 4 5

TEARING PUNCTURE

0 <u>1</u> 2 3 4

 Rinse the gloves in running water before removing, using a neutral detergent if necessary

HYDROCHLOR, ACID 36% KEROSENE



Globus Building 38 Wheel Forge Way Trafford Park, Manchester M17 1EH

Tel: 0161 877 4747 **Fax:** 0161 877 4746 www.globus.co.uk



The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



CAUSTIC SODA 40%

<u>0</u>123456

D - DICHLOROMETHAN F - TOLUENE

<u>0</u>123456

SULPHURIC ACID 96% 0 1 <u>2</u> 3 4 5 6

