OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

1 Identification

Product Identifier

Trade name: Absorb-N-Dry

Product description: Absorbent Clay

Application of the substance / the mixture:

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Balcones Minerals Corporation

233 Balcones Lane (PO Drawer B), Flatonia, TX 78941

361-865-3544 or www.balconesminerals.com for product information

Emergency telephone number: Balcones Minerals: 361-865-3544

2 Hazard(s) identification

Signal Word: Warning

Hazard Statement: Repeated excessive inhalation of dust that exceeds prescribed limits may result in injury to lungs and pulmonary discomfort.

Precautionary Statements

Prevention: Control airborne particulates to level acceptable under PEL/TLV (1 mg/M3) **Response:**

If inhaled, remove person to fresh air and keep comfortable for breathing.

If in eye, flush with water.

Seek medical attention if necessary.

Storage: Keep covered and store in dry, ventilated area.

Disposal: Dispose in compliance with local, state and federal ordinances. Landfills, incinerate or other.

Emergency Overview

This product is a non-combustible, chemically inert mineral. This mineral sample contains naturally-occurring crystalline silica as quartz. Prolonged exposure to respirable crystalline silica may cause lung disease (silicosis). IARC, in Monograph 68, has concluded that crystalline silica inhaled in the form of quartz from occupational sources is carcinogenic to humans (Group 1); however, carcinogenicity was not detected in all industrial circumstances studied. The company is not aware of any scientific or medical data available indicating that exposure to dust from this product under conditions of normal use will cause silicosis or cancer. Adverse effects would not be expected from normal use of this product.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

Trade Name: Absorb-N-Dry

Classification system: NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

NFPA ratings (scale 0 - 4)



Health = 0 Fire = 0 Reactivity = 0

HMIS - ratings (scale 0 - 4)

Health = 0, Fire = 0, Reactivity = 0, Personal Protection: Goggles and Mask Recommended

Composition/information on ingredients

Component	CAS Number	Amount
Fuller's Earth, Calcined	8031-18-3	90-100%
Bentonite, Calcined	1302-78-9	90-100%
Quartz (respirable <1%)	14808-60-7	<10% bulk

May contain some respirable crystalline quartz (dust).

4 First-aid measures

Description of first aid measures

General information: Find ventilation. Remove to fresh air, seek medical help if severe.

After skin contact: No further relevant information available.

After eye contact: Rinse (flush) with water. If severe, seek medical assistance.

After swallowing: No further relevant information available.

Most important symptoms and effects, both acute and delayed: Repeated excessive inhalation of dust that exceeds prescribed limits may result in injury to lungs and pulmonary discomfort.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

Trade Name: Absorb-N-Dry

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

No special measures required.

Special hazards arising from the substance or mixture: No further relevant information

available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use approved dust mask or respirator, if airborne levels exceed PEL/TLV.

Environmental precautions:

Check local, state & federal ordinances. Dispose in compliance with regulations. Landfills, incinerate or other.

Cleanup procedures:

Sweep up or vacuum.

7 Handling and storage

Precautions for safe handling:

Control airborne particulates to level acceptable under PEL/TLV (1 mg/M3)

Practice good housekeeping, follow all suggested regulations, insure ventilation and maintain acceptable levels.

Conditions for safe storage, including any incompatibilities

Storage: Store in dry ventilated area. Keep covered.

8 Exposure controls/personal protection

Components with occupational exposure limits:

14808-60-7 Quartz

PEL 5.0 mg. /M3 TLV 5.0 mg. /M3 NIOSH 0.05 mg. /M3

MSHA 10.0 mg./M3%5:0 242

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

Trade Name: Absorb-N-Dry

Personal Protective Measures:

Respiratory protection:

NIOSH/MSHA Approved respirator: If dust levels exceed PEL/TLV-Adequate ventilation.

Ventilation:

Local Exhaust: Sufficient ventilation to reduce levels

Special: None

Mechanic (General) Reduce levels to equal or below PEL

Other: None

Protective Gloves: Optional if sensitive skin exists

Eye Protection: Recommended (Goggles) Approved

Other protective clothing or equipment: Optional





9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Granules
Color: Tan to white

Odor: None

Odor threshold: Not determined.

pH-value: Inert (approximately 7)

Change in condition

Melting point / freezing point:

Boiling point / boiling range:

Flash point:

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Ignition temperature:

Decomposition temperature: Not applicable.

Auto ignition temperature: Product is not self igniting.

Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

Lower: Upper:

Vapor pressure:Not applicable.Vapor density:Not applicable.

Evaporation rate (Butyl Acetate-1): None.

Relative density:

Solubility: Insoluble.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

Trade Name: Absorb-N-Dry

Partition coefficient (n-octanol/water):

Viscosity:

Not determined.

Not determined.

Approximately 1.5

Other information:No further relevant information available.

10 Stability and reactivity

Reactivity: No further relevant information available.

Chemical stability:

Condition to avoid: Absorbed highly oxidizable liquids, heat build up may occur. Allow time for

mix to cool before packaging or storing in sealable containers.

Incompatible materials: Hydrofluoric acid, vegetable oils, turpentine and unsaturated organic

compounds.

Hazardous polymerization: Will not occur.

11 Toxicological information

Information on toxicological effects

Route of entry: Inhalation

Health Hazards (Acute and Chronic): Repeated excessive inhalation of dust that exceeds prescribed limits may result in injury to lungs and pulmonary discomfort.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

Free crystalline silica according to IARC has exhibited limited evidence of carcinogenicity in animals and humans (over exposure).

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA (Occupational Safety & Health Administration)

None of the ingredients are listed.

Signs and symptoms of exposure: Coughing, labored breathing, pulmonary discomfort. **Medical conditions generally aggravated by exposure:** May affect existing pulmonary and respiratory conditions.

12 Ecological information

Toxicity

Natural earth composition. No further relevant information available.

OSHA HazCom Standard 29 CFR 1910.1200(g), Rev. 2012 and GHS Rev 03.

Printing Date: 3/25/2015

Trade Name: Absorb-N-Dry

13 Disposal considerations

Disposal: Check local, state & federal ordinances. Dispose in compliance with regulations.

Landfills, incinerate or other.

Refer to Section 8.

14 Transport information

DOT Listing: NMFC 48170 Clay, Crushed or Ground in Bags.

15 Regulatory information

No other relevant information.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

Date of preparation / last revision 03/20/15

Abbreviations and acronyms:

PEL: Permissible Exposure Limits

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (US)

HMIS: Hazardous Materials Identification System (USA) MSHA: Mine Safety and Health Administration (USA)

TLV: Threshold Limit Value

NIOSH: National Institute for Occupational Safety and Health

NMFC: National Motor Freight Classification