SAFETY DATA SHEET



1. Identification

Product identifier

Multipurpose & Oneshot Cartridges Ink

Other means of identification

None.

Recommended use

Marking.

Recommended restrictions

None known.

Manufacturer/Importer/Supplier/Distributor information

Company name

Diagraph MSP

Address

5307 Meadowland Parkway Marion IL 62959

Telephone

1-800-521-3047

E-mail

msds@diagraphmsp.com

Contact person

Customer Service

Emergency phone number

Emergency telephone

800-535-5053 (US only)

+1-352-323-3500 international

2. Hazard(s) identification

Physical hazards

Flammable liquids

Category 3

Health hazards

Serious eye damage/eye irritation

Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards

Not classified.

Label elements



Signal word

Warning

Hazard statement

Flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

Response

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Diacetone alcohol	123-42-2	42 - 50	
Titanium dioxide	13463-67-7	0 - 12	

Carbon black	1333-86-4	0 - 9
29H,31H-Phthalocyaninato(2-)- N29,N30,N31,N32 copper	147-14-8	0 -4
2-Methoxy-1-methylethyl acetate	108-65-6	0.5 - 2.0
Other components below reportable levels	, , , , , , , , , , , , , , , , , , ,	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth thoroughly. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed General information Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source

Special protective equipment and precautions for firefighters

of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials. Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Issue date: 13-April-2015

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean up in accordance with all applicable regulations. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid breathing mist or vapor. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Use care in handling/storage.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Store between 35°F (2°C) and 120°F (49°C).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Diacetone alcohol (CAS 123-42-2)	PEL	240 mg/m3	
		50 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	Inhalable fraction.
Diacetone alcohol (CAS 123-42-2)	TWA	50 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper (CAS 147-14-8)	TWA	1 mg/m3	Dust and mist.
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Diacetone alcohol (CAS 123-42-2)	TWA	240 mg/m3	
•		50 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components Type Value 2-Methoxy-1-methylethyl TWA 50 ppm acetate (CAS 108-65-6)

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Colored liquid.

Physical state Liquid. Form Liquid.

Color Various. Odor Characteristic. Odor threshold Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

302 °F (150 °C)

range

Flash point 132.8 °F (56.0 °C)

Evaporation rate Flammability (solid, gas)

Not available. Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

1.4 % v/v

(%)

Flammability limit - upper

8.1 % v/v

(%)

Explosive limit - lower (%) Not available. Not available.

Explosive limit - upper (%)

1.1 hPa (20°C/68°F)

Vapor pressure Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water)

Auto-ignition temperature

Not soluble in water.

Partition coefficient

Not available.

(n-octanol/water)

Not applicable.

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Density

1.21 g/cm3 (20°C/68°F)

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point.

Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Alkali metals, Halogens,

Hazardous decomposition

products

Carbon oxides. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Prolonged or repeated contact may dry skin and cause dermatitis.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May cause respiratory irritation. May cause discomfort if swallowed.

Components Species **Test Results**

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper (CAS 147-14-8)

Acute

Dermal

LD50

Rat

> 5000 mg/kg, 24 hours

Oral

Rat

15000 mg/kg

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

Acute

Dermal

LD50

Rabbit

> 5000 mg/kg

Skin corrosion/irritation

Prolonged or repeated contact may dry skin and cause irritation.

Serious eve damage/eve

irritation

Causes serious eve irritation.

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

Inhalation of carbon black or titanium dioxide dust may cause cancer, however due to the physical

form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) Titanium dioxide (CAS 13463-67-7)

Version #: 01 Revision date: -

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Issue date: 13-April-2015

Multipurpose & Oneshot Cartridges Ink

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

No data available.

Chronic effects

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. The product contains organic solvents which may be absorbed into the body by skin contact and

cause permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity

The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data available. No data available.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diacetone alcohol (CAS 123-42-2)

-0.098

Mobility in soil

The product is insoluble in water. Expected to have low mobility in soil.

Other adverse effects

None known.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

D001: Waste Flammable material with a flash point <140 °F

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of waste and residues in accordance with local authority

requirements.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number

UN1210

UN proper shipping name

Printing ink, flammable

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Packing group Ш

Special provisions

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions

B1, IB3, T2, TP1 150

Packaging non bulk

173

Packaging bulk

IATA **UN** number 242

UN1210

UN proper shipping name

Printing ink flammable

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3 Packing group **]**|| **Environmental hazards** No **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Multipurpose & Oneshot Cartridges Ink

SDS US

6/8

IMDG

UN number UN1210

UN proper shipping name PRINTING INK FLAMMABLE

Transport hazard class(es)

Class 3 Subsidiary risk Label(s) 3

Packing group Ш

Environmental hazards

Marine pollutant No **EmS** F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is hazardous according to OSHA 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA Hazardous Substances - Not applicable.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper LISTED (CAS 147-14-8)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2) Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper (CAS 147-14-8)

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2)

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4) Diacetone alcohol (CAS 123-42-2) Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region

Inventory name

On inventory (yes/no)*

Canada

Domestic Substances List (DSL)

Yes

Canada

Non-Domestic Substances List (NDSL)

No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

13-April-2015

Revision date

Version #

Further information

HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings

Health: 2 Flammability: 2

Physical hazard: 0

NFPA ratings



Disclaimer

Diagraph MSP cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Multipurpose & Oneshot Cartridges Ink 908088 Version #: 01 Revision date: -

SDS US Issue date: 13-April-2015

8/8