

1. Identification

Product identifier Markers, GPX Classic, 2018P, Grizzly (All Colors)

Other means of identification None.

Recommended use Marking.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Diagraph MSP
Address 5307 Meadowland Parkway Marion IL 62959
Telephone 1-800-521-3047
E-mail msds@diagraphmsp.com
Contact person Customer Service
Emergency phone number Emergency telephone 800-535-5053 (US only)
+1-352-323-3500 international

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, dermal Category 4
Acute toxicity, inhalation Category 4
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2
Carcinogenicity Category 2
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation
Specific target organ toxicity, repeated exposure Category 2 (Central nervous system, Liver, Kidney)
Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure. Toxic to aquatic life.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response	If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Xylene (mix)	1330-20-7	40-80
Titanium dioxide	13463-67-7	0-30
Ethylbenzene	100-41-4	5-20
1-Methoxy-2-propanol	107-98-2	0-20
Carbon black	1333-86-4	0-10
Cumene	98-82-8	< 1
Benzene	71-43-2	< 0.1
Naphthalene	91-20-3	< 0.1
Toluene	108-88-3	< 0.1

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Abdominal pain. Decrease in motor functions. Behavioral changes. Narcosis. Dizziness. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Jaundice. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Edema. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Storage temperature: between 2 and 49°C. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Cumene (CAS 98-82-8)	PEL	245 mg/m3	
Ethylbenzene (CAS 100-41-4)	PEL	50 ppm	
		435 mg/m3	
		100 ppm	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (mix) (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
	TWA	50 ppm	
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	Inhalable fraction.
Cumene (CAS 98-82-8)	TWA	50 ppm	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Xylene (mix) (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m3
		150 ppm
	TWA	360 mg/m3
		100 ppm
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3
Cumene (CAS 98-82-8)	TWA	245 mg/m3
		50 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
Xylene (mix) (CAS 1330-20-7)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (mix) (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

1-Methoxy-2-propanol (CAS 107-98-2)

Can be absorbed through the skin.

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Cumene (CAS 98-82-8)

Skin designation applies.

US - Tennessee OELs: Skin designation

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Cumene (CAS 98-82-8)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid.

Color

According to product specification.

Odor

Characteristic.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

248 °F (120 °C)

Flash point

75.2 °F (24.0 °C)

Evaporation rate

Not available.

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1 % v/v

Flammability limit - upper (%)

7.8 % v/v

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

9.5 hPa at 20°C.

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)	
Solubility (water)	Fully miscible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin contact	Harmful in contact with skin. Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics	Abdominal pain. Behavioral changes. Decrease in motor functions. Narcosis. Dizziness. Nausea, vomiting. Jaundice. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Edema.
---	---

Information on toxicological effects

Acute toxicity	Harmful if inhaled. Harmful in contact with skin. May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
1-Methoxy-2-propanol (CAS 107-98-2)		
Acute		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg
<i>Inhalation</i>		
LC50	Mouse	6000 - 7000 ppm, 6 Hours
<i>Oral</i>		
LD50	Rat	3739 mg/kg
Cumene (CAS 98-82-8)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 3160 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	8000 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	2910 mg/kg

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	15400 mg/kg
<i>Inhalation</i>		
LC50	Rat	17.4 mg/m ³ , 4 Hours
<i>Oral</i>		
LD50	Rat	35000 - 47000 mg/kg
Xylene (mix) (CAS 1330-20-7)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12126 mg/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	6350 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	3523 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer. Inhalation of carbon black or titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Cumene (CAS 98-82-8)	2B Possibly carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Xylene (mix) (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure May cause damage to organs (Central nervous system, Liver, Kidney) through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Components	Species	Test Results
Cumene (CAS 98-82-8)		
Aquatic		
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.7 mg/l, 96 hours

Components		Species	Test Results
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Daphnia	1.81 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	32 - 88 mg/l, 96 hours
		Fathead minnow (Pimephales promelas)	12.1 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylbenzene (CAS 100-41-4)	3.15
Xylene (mix) (CAS 1330-20-7)	3.2

Mobility in soil The product is miscible with water. May spread in water systems.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1210
UN proper shipping name	Printing ink, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	B1, IB3, T2, TP1
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN1210
UN proper shipping name	Printing ink flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	No
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1210
UN proper shipping name	PRINTING INK FLAMMABLE

Transport hazard class(es)**Class** 3**Subsidiary risk** -**Label(s)** 3**Packing group** III**Environmental hazards****Marine pollutant** No**EmS** F-E, S-D**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to** Not established.**Annex II of MARPOL 73/78 and****the IBC Code**

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

1-Methoxy-2-propanol (CAS 107-98-2) LISTED

Cumene (CAS 98-82-8) LISTED

Ethylbenzene (CAS 100-41-4) LISTED

Xylene (mix) (CAS 1330-20-7) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Xylene (mix)	1330-20-7	40-80
Ethylbenzene	100-41-4	5-20
Cumene	98-82-8	< 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Xylene (mix) (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. Massachusetts RTK - Substance List**

1-Methoxy-2-propanol (CAS 107-98-2)

Carbon black (CAS 1333-86-4)

Cumene (CAS 98-82-8)

Ethylbenzene (CAS 100-41-4)

Titanium dioxide (CAS 13463-67-7)

Xylene (mix) (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

1-Methoxy-2-propanol (CAS 107-98-2)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Xylene (mix) (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1-Methoxy-2-propanol (CAS 107-98-2)
Carbon black (CAS 1333-86-4)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Titanium dioxide (CAS 13463-67-7)
Xylene (mix) (CAS 1330-20-7)

US. Rhode Island RTK

Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Xylene (mix) (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzene (CAS 71-43-2)
Cumene (CAS 98-82-8)
Ethylbenzene (CAS 100-41-4)
Naphthalene (CAS 91-20-3)
Toluene (CAS 108-88-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 21-May-2015
Revision date -
Version # 01
HMIS® ratings Health: 2*
Flammability: 3
Physical hazard: 0

NFPA ratings

Disclaimer

Diagraph MSP cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.