# DOLL

# SAFETY DATA SHEET

# 1. Identification

Product identifier KOOL ALL

METALWORKING FLUID

Other means of identification

SDS number Not applicable

Recommended use METALWORKING FLUID

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name DOALL SAWING PRODUCTS

A DOALL COMPANY 2375 Toughy Avenue Elk Grove Village, IL 60007

Telephone (General

Information)

Emergency telephone

number

Emergency telephone number (outside USA)

888-362-5572, Ext 65047

1-800-424-9300 (CHEMTREC)

1-703-527-3887 (CHEMTREC)

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin irritationCategory 2

Serious eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.

**Precautionary statement** 

**Prevention** Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Wear eye protection/face protection. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off

contaminated clothing and wash before reuse.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: KOOL ALL SDS US

3.33% of the mixture consists of component(s) of unknown acute oral toxicity. 3.33% of the mixture consists of component(s) of unknown acute dermal toxicity.

Use in manufacturing processes only.

The classified hazards shown on this SDS are associated with the product concentrate. These hazards are not expected under recommended use conditions and dilution.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES		64742-52-5	10 - 20
DIETHYLENE GLYCOL MONOBUTYL ETHER		112-34-5	3 - 5
MONOETHANOLAMINE		141-43-5	1 - 3
TRIAZINETRIETHANOL		4719-04-4	1 - 3
TRIETHANOLAMINE		102-71-6	1 - 3
Other components below reportab	le levels		70 - 80

The exact percentages of hazardous ingredients have been withheld as a trade secret.

### 4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist. Under normal conditions of intended use, this material is not expected to be an inhalation hazard.
Skin contact	Rinse skin with water. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

**Eye contact**Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists

attention if irritation develops and persists.

**Ingestion** Rinse mouth thoroughly. Do not give liquids. Do not induce vomiting. If vomiting occurs, keep head

low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel

unwell.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

If exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media

Foam. Dry chemical powder. Carbon dioxide (CO2). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear suitable protective equipment.

and precautions for firefighte Fire fighting

equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

General fire hazards No unusual fire or explosion hazards noted.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Local authorities should be advised if significant spillages cannot be contained. This product is miscible in water. Clean up in accordance with all applicable regulations.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Contact local authorities in case of spillage to drain/aquatic environment. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

# 7. Handling and storage

Precautions for safe handling

Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). Do not allow material to freeze. If frozen, product may separate. Thaw completely at room temperature and stir thoroughly prior to use.

Value

# 8. Exposure controls/personal protection

## **Occupational exposure limits**

U.S. - OSHA

	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	PEL	5 mg/m3	
US. OSHA Table Z-1 Limits for Air			
	Туре	Value	
MONOETHANOLAMINE (CAS 141-43-5)	PEL	6 mg/m3	
		3 ppm	
U.S NIOSH			
	Туре	Value	
SEVERELY-HYDROTREAT ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)	STEL	10 mg/m3	
,	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to Chen	nical Hazards		
	Туре	Value	
MONOETHANOLAMINE (CAS 141-43-5)	STEL	15 mg/m3	
,		6 ppm	
	TWA	8 mg/m3	
		3 ppm	
		o pp	

Material name: KOOL ALL SDS US

## **ACGIH**

Type Value

SEVERELY-HYDROTREAT TWA 5 mg/m3

ED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

**US. ACGIH Threshold Limit Values** 

	Type	Value	Form
DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
MONOETHANOLAMINE (CAS 141-43-5)	STEL	6 ppm	
	TWA	3 ppm	
TRIETHANOLAMINE (CAS 102-71-6)	TWA	5 mg/m3	

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Do not get in eyes. Eye wash fountain is

recommended.

Skin protection

**Hand protection** Nitrile gloves are recommended.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get in eyes, on skin, on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

# 9. Physical and chemical properties

Appearance CLEAR
Physical state Liquid.
Form Liquid.

ColorNot available.OdorCHEMICALOdor thresholdNot available.

**pH** 9.8

Melting point/freezing point  $< 32 \degree F (< 0 \degree C)$ Initial boiling point and boiling  $> 212 \degree F (> 100 \degree C)$ 

range

Flash point Not Applicable

**Evaporation rate** Like water when diluted

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Material name: KOOL ALL SDS US

Vapor density Not available.

Relative density Not available.

Solubility(ies) 100 % Water Miscible

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

pH in aqueous solution 9.6 @ 5%

Specific gravity 1.009

VOC ASTM D2369 13 %

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid** Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents.

**Hazardous decomposition** 

products

Smoke, fumes, and oxides of carbon

## 11. Toxicological information

## Information on likely routes of exposure

Inhalation Not classified.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes eye irritation.

**Ingestion** Not classified.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause an allergic skin reaction.

#### Information on toxicological effects

**Acute toxicity** 

Components Species Test Results

MONOETHANOLAMINE (CAS 141-43-5)

Acute Dermal

LD50 Rabbit 1025 mg/kg

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

<u>Acute</u>

**Dermal** *Liquid* 

LD50 Rabbit > 5000 mg/kg

Inhalation

Mist

LC50 Rat 5.7 mg/l, 4 hours

**Oral** *Liquid* 

LD50 Rat > 5000 mg/kg

Material name: KOOL ALL SDS US

Components Species Test Results

TRIAZINETRIETHANOL (CAS 4719-04-4)

Acute
Dermal
Liquid

LD50 Rat 4000 mg/kg

**Oral** Liquid

LD50 Rat 1000 mg/kg

TRIETHANOLAMINE (CAS 102-71-6)

Acute
Dermal
Liquid

LD50 Rabbit > 2000 mg/kg

**Oral** *Liquid* 

LD50 Rat 4190 mg/kg

Skin corrosion/irritation Serious eye damage/eye Causes skin irritation. Causes eye irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

TRIETHANOLAMINE (CAS 102-71-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects Not classified.

**Further information** The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

12. Ecological information

**Ecotoxicity** Contains a substance which causes risk of hazardous effects to the environment.

Components Species Test Results

DIETHYLENE GLYCOL MONOBUTYL ETHER (CAS 112-34-5)

Aquatic

Acute

Crustacea EC50 Daphnia > 100 mg/l, 48 hours
Fish LC50 Bluegill (Lepomis macrochirus) 1300 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Components Species Test Results

MONOETHANOLAMINE (CAS 141-43-5)

**Aquatic** 

Fish LC50 Rainbow trout, donaldson trout 114 - 196 mg/l, 96 hours

(Oncorhynchus mykiss)

Acute

Crustacea EC50 Daphnia 65 mg/l, 48 hours ECHA

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

Aquatic

Acute

Fish LC50 Fish > 100 mg/l, 96 hours

TRIAZINETRIETHANOL (CAS 4719-04-4)

**Aquatic** 

Acute

 Crustacea
 EC50
 Daphnia
 11.9 mg/l, 48 hours ECHA

 Fish
 LC50
 Fish
 16 - 240 mg/l, 96 hours ECHA

TRIETHANOLAMINE (CAS 102-71-6)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 565.2 - 658.3 mg/l, 48 hours

Acute

Fish LC50 Bluegill (Lepomis macrochirus) 450 - 1000 mg/l, 96 hours

# Persistence and degradability

# **Bioaccumulative potential**

Partition coefficient n-octanol / water (log Kow)

DIETHYLENE GLYCOL MONOBUTYL ETHER 1
MONOETHANOLAMINE -1.31
TRIAZINETRIETHANOL -2
TRIETHANOLAMINE -2.3

**Bioconcentration factor (BCF)** 

MONOETHANOLAMINE < 3.2, ESTIMATED

**Mobility in soil** This product is miscible in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. It may be reportable under the provisions of SARA Sections 311

and 312 if specific threshold criteria are met or exceeded.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

TRIAZINETRIETHANOL (CAS 4719-04-4)

1.0 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.DIETHYLENE GLYCOL MONOBUTYL ETHER112-34-53 - 5

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

## **US** state regulations

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

DIETHANOLAMINE (CAS 111-42-2) Listed: June 22, 2012

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

DIETHANOLAMINE (CAS 111-42-2)

SEVERELY-HYDROTREATED NAPHTHENIC PETROLEUM DISTILLATES (CAS 64742-52-5)

California South Coast Air Quality Management District (SCAQMD) Rule 1144 (VOC Emissions) This product is subject to SCAQMD Rule 1144; it is compliant and may be sold and used in the SCAQMD. The VOC content of the product is 73 g/L, measured by ASTM Method E-1868-10. This product has a specified use dilution VOC limit of  $\,$  75 g/L, the maximum dilution concentration is

100 % to maintain compliance.

**US. California Proposition 65** 

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### International Inventories

Country(s) or regionInventory nameOn inventory or exempt (yes/no)\*AustraliaAustralian Inventory of Chemical Substances (AICS)NoCanadaDomestic Substances List (DSL)Yes

Country(s) or region	Inventory name	On inventory or exempt (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*	and in a state of the circumstance of the control o	n./a\

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

# 16. Other information, including date of preparation or last revision

 Issue date
 03-11-2015

 Revision date
 05-24-2018

Version # 05

Further information Not available.

NFPA ratings Health: 1
Flammability: 0
Instability: 0

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

Material name: KOOL ALL SDS US