
# DUPONT<sup>™</sup> TYCHEM® 4000 SL125B WH

# **GARMENT TECHNICAL DATA SHEET**



#### This picture is for measurement reference only.

### **Customer Service:**

United States 1-800-931-3456

Canada 1-800-387-9326

## SafeSpec Home Page

Seams and closures have less barrier than fabric. Note: for protection from hazardous or infectious liquids, additional barrier tests are required to establish suitability for use. CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under the specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures may provide less barrier than the fabric. If the fabric becomes torn, abraded, or punctured, end-user should discontinue use of garment to avoid compromising the barrier protection. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTES, EXPRESSED OR MIPLIED, INCLUDING WITHOUT LIMITATION NO WARRANTES OF MERCHANTABLITY OR FITNESS FOR A PARTICULAR USE AND ASSUME NO LIABILITY IN CONVECTION WITH ANY OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infinge any patent, trademark or technical information of DuPont or others covering any material or its use. Data presented does not comprise a product specification.

Warning: Cleanroom apparel should not be used around heat, flames, sparks or in potentially flammable or explosive environments. Cleanroom fabrics should have slipering could and the outer sole of boots, shoe covers, or other gament surfaces in conditions where slipping could occur.

Silicone Statement: In the past, DuPont has found that threads and zippers can be the most significant source of silicone oil contamination in garments. DuPont specifies that thread and zippers used in DuPont<sup>\*M</sup> Tyvek® IsoClean® and ProClean® garments be manufactured without the use of silicone oils. For end uses with concerns about contamination with silicone oils or any other contaminants, the best practice is to audit inbound materials, including garments, for those contaminants.

Latex Statement: As of January 1, 2006, DuPont production specifications exclude use of components containing natural rubber latex in the manufacture of DuPont<sup>TM</sup> Tyvek® (soClean® and ProClean® garments. Anyone who begins to exhibit allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at 1.800.441.3637.

Measurements are approximate values intended to assist in proper size selection. Normal variability may result in slight differences in actual garment sizes.

Copyright © 2013 DuPont. All rights reserved. The DuPont Oval Logo, DuPont<sup>™</sup>, The miracles of science<sup>™</sup>, and all products denoted with © or <sup>™</sup> are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its atilitates. Printed on : November 5, 2018

PRODUC	T INFORMA	ΓΙΟΝ				
ATTRIBUTES	ATTRIBUTES DuPont <sup>™</sup> Tychem® 4000 Coverall. Collar. Elastic Wrists and Ankles. Storm Flap with Adhesive Closure. Bound Seams. White.					
CATALOG NUMBER SL125BWHxx0012yy (xx=size;yy=option code) When ordering, replace xx with desired size.						
FABRIC	DESIGN	SEAM	COLOR	CASE COUNT	SIZES	OPTION CODES
Tychem® 4000	Coverall w/ Elastic Wrists and Ankles	Bound	White	12 per case	MD, LG, XL, 2X, 3X, 4X, 5X, 6X	00
TYPICAL FINISHED DIMENSIONS						
			SIZES		PART NUMBER	
OPTION C	CODE DES	SCRIPTION	s	IZES	PART NUM	IBER
<b>OPTION C</b> 00		SCRIPTION Standard	MD, LG,	B <b>IZES</b> XL, 2X, 3X, 5X, 6X	PART NUM	
00		standard	MD, LG, 4X,	XL, 2X, 3X, 5X, 6X		(001200
00 PHYSICA	S	Standard	MD, LG, 4X,	XL, 2X, 3X, 5X, 6X	SL125BWHx>	x001200
00 PHYSICA PR	S AL PROPERT	itandard IES - FAI	MD, LG, 4X, BRIC DAT	XL, 2X, 3X, 5X, 6X	SL125BWHxx	x001200
00 PHYSICA PR Th	S AL PROPERT ROPERTY	itandard IES - FAI	MD, LG, 4X, BRIC DAT	XL, 2X, 3X, 5X, 6X FA D	SL125BWHxx Typical values, not RESULT	<001200 <p>specifications.</p>
00 PHYSICA PR Th Bas	S AL PROPERT ROPERTY nickness	itandard IES - FAI	MD, LG, 4X, BRIC DAT TEST METHO ASTM D177	XL, 2X, 3X, 5X, 6X FA D 7 6	SL125BWHxx Typical values, not RESULT 12 mils	<001200 <p>specifications.</p>
00 PHYSICA PR Th Bas Burst Str	S AL PROPERT ROPERTY nickness sis Weight	itandard IES - FAI	MD, LG, 4X, BRIC DAT TEST METHO ASTM D177 ASTM D377	XL, 2X, 3X, 5X, 6X TA D 7 6 6	SL125BWHxx Typical values, not RESULT 12 mils 3.6 oz/yd	<001200 specifications.
00 PHYSICA PR Th Bas Burst Str Breaking Str	S AL PROPERT ROPERTY hickness sis Weight rength - Mullen	itandard IES - FAI	MD, LG, 4X, BRIC DAT TEST METHO ASTM D177 ASTM D377 ASTM D378	XL, 2X, 3X, 5X, 6X <b>FA</b> <b>D</b> 7 6 6 4	SL125BWHxx Typical values, not RESULT 12 mils 3.6 oz/yd 73 psi	<001200 specifications.