

# EVERLUBE<sup>®</sup> PRODUCTS

## SAFETY DATA SHEET

EVERLUBE 620

Page 1 of 8

### 1. IDENTIFICATION:

PRODUCT NAME: EVERLUBE 620  
PRODUCT CODE: PEV620  
PRODUCT USE.: Low Friction Coating

HMIS CODES H F R P  
2\*3 0 G

#### Manufacturer:

EVERLUBE PRODUCTS  
100 COOPER CIRCLE  
PEACHTREE CITY, GA 30269

EMERGENCY PHONE (24 hours): CHEMTREC - 800-424-9300  
INFORMATION PHONE (8:00 a.m - 5:00 p.m EST): (770) 261-4800  
NAME OF PREPARER: CHEMICAL COMMUNICATIONS COORDINATOR  
DATE PREPARED: 9/9/2014

### 2. HAZARDS IDENTIFICATION



#### Classification:

HIGHLY FLAMMABLE LIQUID AND VAPOUR - Category 2

#### Signal Word:

DANGER

#### HAZARDS STATEMENTS:

H305-May be harmful if swallowed and enters airways.

H316-Causes mild skin irritation

H320-Causes eye irritation

H333,H336-May be harmful if inhaled; May cause drowsiness or dizziness

H360-Suspected of damaging fertility or the unborn child.

#### PRECAUTIONARY STATEMENTS:

P210-Keep away from heat/sparks/open flames/hot surfaces - No smoking

P242-Use only non-sparking tools.

P280-Wear protective gloves/eye protection/face protection.

P403-P233-Store in well-ventilated place. Keep container tightly closed.

P501-Dispose of contents/container in accordance with  
local/regional/national/regulation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#

% BY WT.

ETHANOL

64-17-5

30% - 35%

## SAFETY DATA SHEET

OSHA PEL 1000.000 ppm - TWA OSHA VPEL 1000.000 ppm - TWA ACGIH TLV 1000.000 ppm - TWA LD50 ORAL-7060 mg/kg (rat) LC 50 INHALATION-20000 ppm 10 hr (rat)		
TOLUENE	108-88-3	20% - 25%
OSHA PEL 200.00 PPM-TWA OSHA PEL 300.000 PPM-CEILING OSHA VPEL 100.000 PPM-TWA OSHA VPEL 150.000 PPM-STEL (SKIN) ACGIH TLV 50.000 PPM-TWA (SKIN) ACGIH TLV 150.000 PPM-STEL (SKIN) LD 50 ORAL RAT: 2.6G/KG LC 50 INHALATION RAT: 8000 PPM; 4 H LD 50 DERMAL RABBIT: 12,124 MG/KG		
MOLYBDENUM DISULFIDE	1317-33-5	20% - 25%
ACGIH TWA I 10MG/M3 ACGOH TWA R 3 MG/M3 LD50/LC50: 500 mg Acute Oral (rats)		
ISOPROPANOL	67-63-0	0% - 5%
ACGIH TWA: 200 ppm ACGIH STEL: 400 ppm NOISH REL: 400 ppm NOISH REL: 980 mg/m3 NOISH STEL: 500 ppm NOISH STEL: 1,225 mg/m3 OSHA Z1 PEL: 400 ppm OSHA Z1 PEL: 980 mg/m3 LC50 INHALATION: 16000ppm 4hr (rat)		
METHYL ALCOHOL	67-56-1	0% - 5%
OSHA PEL 200.000 ppm-TWA OSHA VPEL 200.000 ppm-TWA (Skin) OSHA VPEL 500.000 ppm-STEL (Skin) ACGIH TLV 200.000 ppm-TWA (Skin) ACHIH TLV 250.000 ppm-STEL (Skin) LD50 ORAL 1000.0 mg/kg (man) LC50 VAPORS 1600 ppm (rats)		
PHENOL	108-95-2	0% - 5%
ACGIH TLV-TWA 5 ppm (Skin) ACGIH TLV-TWA 19 mg/m3 (8hr) OSHA PEL-TWA 5 ppm (skin) OSHA PEL TWA 19 mg/m3 (8hr) LC50 Inhalation Vapor Rat 316 mg/m3 4 hr LD50 Dermal Rabbit 630 mg/kr LD50 Dermal Rat 69 mg/kg LD50 Oral Rat 317 mg/kg		

### 4. First Aid Measures

#### Eyes:

With eyelids open, immediately flush eyes with lots of lukewarm water for at least 30 minutes. Get immediate medical assistance.

#### Skin:

Wash the skin thoroughly with plenty of water for at least 15 minutes, using a mild and non-abrasive soap. Cold water may be used.

#### Ingestion:

Never give anything by mouth if the victim is semi-conscious,

## SAFETY DATA SHEET

unconscious, or convulsing.

### Inhalation:

Evacuate to fresh air and administer artificial respiration if breathing stopped. Obtain medical aid.

## 5. Fire Fighting Measures

---

### Flammable Properties:

Flash Point (Degree F) .....: 40 F

Flash Point Method .....: TCC

### Explosive Limits:

Upper explosive limit: 36.0

Lower explosive limit: 1.2

### Hazardous Combustion Products:

Carbon, Sulfur, or their compounds

### Extinguishing Media:

CO<sub>2</sub>, foam, dry chemical or halon

### Firefighting Procedures:

Fire-Fighters should wear self-contained breathing apparatus and full protective equipment.

Extinguish all nearby sources of ignition.

## 6. Accidental Release Measures

---

### Small Spill:

Eliminate all sources of ignition, provide ventilation, contain spill, and absorb with inert absorbent.

Wear appropriate breathing apparatus (if applicable) and protective clothing.

Use only non-sparking tools and equipment.

### Large Spill:

Remove by mechanical means and place in containers.

Use only non-sparking tools and equipment.

### Environmental Precautions:

Prevent the product or the wash waters from entering the water system or sewers.

US regulations require reporting spills of this material that could reach any surface waters. In Canada, report to the applicable provincial environment ministry.

## 7. Handling and Storage

---

### Handling:

Avoid breathing dust/fume/gas/mist/vapours/spray.

Do not get in eyes, on skin, or on clothing.

Wash contaminated clothing thoroughly after handling.

## SAFETY DATA SHEET

Wash skin thoroughly (with soap and water) after handling.

### Storage:

Store in a cool, dry well ventilated place, away from incompatible materials.

Store in a closed/sealed container.

Keep away from heat, sparks, flame, and ignition source.

## 8. Exposure Controls/Personal Protection

---

### Airborne Exposure Limits:

Mixture, see section 3

### Engineering Controls:

General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below the threshold limit values.

Use explosion-proof electrical/ventilating/lighting equipment

Avoid breathing dust/fumes/gas/mist/vapours/spray

Effective exhaust ventilation should always be provided to draw fumes, vapors or dust away from workers to prevent routine inhalation.

### Personal Protective Equipment:



### Respiratory Protection:

In case of inadequate ventilation, wear respiratory protection.

Use NIOSH/MSHA approved Cartridge Respirator or Mask to keep airborne mists and concentrations below the time weighted threshold limit values.

### Skin Protection:

Wear protective gloves (eg Neoprene or Nitrile) for skin protection.

### Eye Protection:

Wear eye protection/face protection. Contact lenses should not be worn without goggles.

## 9. Physical and Chemical Properties

---

Flammability (solid, gas).....: Data not available

Boiling Point .....: 147 F

Melting Point .....: Data not available

VOC.....: 695 grams/liter

Freezing Point .....: Data not available

Flash Point .....: 40 F

Vapor Pressure .....: Data not available

Vapor Density .....: Heavier than air.

Solubility in Water .....: Slightly Soluble

Density.....: 9.2 lb/gl

Evaporation Rate .....: Faster than n-Butyl Acetate.

## SAFETY DATA SHEET

**Explosive Limits:**

Upper Explosive Limit .....: 36.0

Lower Explosive Limit .....: 1.2

Specific Gravity .....: 1.10487

PH .....: None Known

Volatile (% by Weight).....: 65%

Appearance and Odor .....: Gray/Black liquid, organic solvent odor

Odor Threshold .....: Not applicable

Viscosity .....: Not applicable

Partition Coefficient:.....: Data not available

Decomposition Temperature ...: Data not available

Autoignition temperature.....: Data not available

**10. Stability and Reactivity**

---

**Chemical Stability (Conditions to Avoid):**

Stable under normal conditions.

**Incompatibility:**

Oxidizers, Strong Acids or Alkalies.

**Hazardous Decomposition Products:**

Irritating and/or toxic fumes including the following may be released:

Carbon, Sulfur, or their compounds

**Hazardous Polymerization:**

Will not occur.

**11. Toxicological Information**

---

**Acute Toxicity Values:**

Mixture, see section 3 - Hazardous Ingredients

**Germ Cell Mutagenicity:**

Data not available.

**Chronic/Carcinogenicity:**

IARC (International Agency for Research of Cancer):

Group 3-Not classified as a cancer causing agent in humans

NTP (National Toxicology Program):

Not listed as a carcinogen

**Reproductive Toxicity:**

This product contains chemical(s) suspected of damaging fertility or the unborn child

**STOT-single exposure:**

Data not available

**STOT-repeated exposure:**

Data not available

**Aspiration Hazard:**

The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 ml/Kg has been ingested, vomiting should be induced with supervision. If symptoms, such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

## SAFETY DATA SHEET

**Routes of Exposure:**

Ingestion: May be harmful if swallowed and enters airways.

Skin: Causes mild skin irritation

Eye: Causes eye irritation

Inhalation: May be harmful if inhaled; May cause drowsiness or dizziness

**12. Ecological Information**

---

**Environmental Fate:**

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Canadian and U.S. regulations require that environmental and/or other agencies be notified of a spill incident. The spill area must be cleaned and restored to the original condition or to the satisfaction of authorities.

**Environmental Toxicity:**

None Known

**Persistence and Degradability:**

None Known

**Bioaccumulative Potential:**

None Known

**Mobility in Soil**

None Known

**Other Adverse Effects:**

None Known

**13. Disposal Considerations**

---

**Disposal Methods:**

Dispose of contents/container to: A licensed waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licensed waste disposal site with approval of environment authority.

**14. Transport Information**

---

Domestic (Land, DOT), International (Water, IMO/IMDG), International (Air, ICAO) Road and Rail (ADR/RID), Air (ICAO/IATA), Vessel (IMO/IMDG):

**UN Number:**

UN1263

**UN Shipping Name:**

PAINT RELATED MATERIAL

**Transport Hazard Class:**

Class 3



**Packing Group:**  
Group II

**ENVIRONMENTAL HAZARDS:**

**Marine Pollutant:**  
Not known to be a marine pollutant

**Special Precautions for User:**  
None Known

**15. Regulatory Information**

---

**U.S. Federal Regulations:**

**OSHA:**  
OSHA Regulated

**TSCA:**  
ALL COMPONENTS OF THIS PRODUCT ARE ON THE TSCA INVENTORY OR ARE  
EXTINCT FROM REQUIREMENTS

**CERCLA: SARA Hazard Category:**

**Section 313:**  
IF THIS MATERIAL HAS ANY COMPONENTS THAT ARE REPORTABLE UNDER SARA 313  
THEY ARE SHOWN IN THE FOLLOWING LISTING. IF THE LISTING IS BLANK, THERE  
ARE NO REPORTABLE COMPONENTS.

COMPONENT	CAS #	% BY WT.
ETHANOL	64-17-5	30% - 35%
TOLUENE	108-88-3	20% - 25%
METHYL ALCOHOL	67-56-1	0% - 5%
PHENOL	108-95-2	0% - 5%

**FRANK DODD SECTION 1502:**  
ALL COMPONENTS OF THIS PRODUCT COMPLY WITH TITLE 15 OF THE US CONSUMER  
FINANCIAL PROTECTION ACT, DODD-FRANK ACT SECTION 1502 (CONFLICT  
MINERALS ACT).

**State Regulations:**

**California Prop 65:**  
This product contains a chemical known to the State of California to  
cause birth defects or other reproductive harm.

**International Regulations:**

**WHMIS Classification:**  
B2, D2A, D2B,

**SAFETY DATA SHEET****CEPA (Canadian Environmental Protection Act)**

ALL INGREDIENTS ARE CEPA APPROVED FOR IMPORT TO CANADA. THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CONTROLLED PRODUCTS REGULATION (CPR) AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

**EINECS (European Inventory of Existing Chemical List)**

ALL COMPONENTS OF THIS PRODUCT ARE INCLUDED ON THE EUROPEAN INVENTORY OF EXISTING CHEMICALS LIST

**16. Other Information**

---

**Manufacturer Disclaimer:**

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION AND RECOMMENDATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE AT THE TIME OF PREPARATION OR OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE. HOWEVER, IT IS THE USERS RESPONSIBILITY TO DETERMINE SAFETY, TOXICITY, AND SUITABILITY FOR HIS OWN USE OF THE PRODUCT. EVERLUBE PRODUCTS ASSUMES NO RESPONSIBILITY. THE CUSTOMER OR RECIPIENT OF THIS SDS SHOULD ENSURE THAT THE INFORMATION CONTAINED IN THIS SDS IS MADE AVAILABLE TO ALL EMPLOYEES OR OTHER PERSONS WHOM HE KNOWS OR BELIEVES WILL USE THIS MATERIAL

[www.everlubeproducts.com](http://www.everlubeproducts.com)