Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	:	MISTY DRY DEODORIZERS SPRING RAIN
Material number	:	0000000001001870
Manufacturer or supplier's	deta	ails
Company	:	Zep Inc.
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137
Telephone	:	404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless
Odour	odourized

GHS Classification

Flammable aerosols Gases under pressure Eye irritation Specific target organ toxicity - single exposure	 Category 1 Liquefied gas Category 2A Category 3 (Central nervous system)
GHS label elements	
Hazard pictograms	Flame Gas cylinder Exclamation
Signal word	: Danger

Version 2.2	Revision Date 09/17/2020	Print Date 03/20/2021
Hazard statements	 H222 Extremely flammable aero H280 Contains gas under pressu H319 Causes serious eye irritatio H336 May cause drowsiness or 	ure; may explode if heated. on.
Precautionary statements	 Prevention: P210 Keep away from heat/spar No smoking. P211 Do not spray on an open fl P251 Pressurized container: Do use. P261 Avoid breathing dust/ fume P264 Wash skin thoroughly after P271 Use only outdoors or in a w P280 Wear eye protection/ face Response: P304 + P340 + P312 IF INHALE and keep comfortable for breathin CENTER/doctor if you feel unwe P305 + P351 + P338 IF IN EYES for several minutes. Remove cor easy to do. Continue rinsing. P337 + P313 If eye irritation pers attention. Storage: P403 + P233 Store in a well-ven tightly closed. P410 + P412 Protect from sunlig temperatures exceeding 50 °C/ ~ Disposal: P501 Dispose of contents/contai regulation. 	ame or other ignition source. not pierce or burn, even after e/ gas/ mist/ vapours/ spray. r handling. well-ventilated area. protection. D: Remove person to fresh air ing. Call a POISON ell. S: Rinse cautiously with water ntact lenses, if present and sists: Get medical advice/ tilated place. Keep container th. Do not expose to 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
acetone	67-64-1	>= 70 - < 90
propane	74-98-6	>= 10 - < 20
butane	106-97-8	>= 10 - < 20

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Get medical attention.

Version 2.2	Revision Date 09/17/2020	Print Date 03/20/2021
If inhaled	: Consult a physician after significa If unconscious, place in recovery advice.	
In case of skin contact	 Remove contaminated clothing ar Wash contaminated clothing befo Wash off immediately with soap a If skin irritation persists, call a phy 	re reuse. Ind plenty of water.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing If eye irritation persists, consult a Rinse immediately with plenty of v for at least 15 minutes. 	specialist.
If swallowed	: Keep respiratory tract clear. Never give anything by mouth to a If symptoms persist, call a physici DO NOT induce vomiting unless of physician or poison control center	an. directed to do so by a
Most important symptoms and effects, both acute and delayed	 Chronic effects are delayed and sobserved during an exposure. Effects are dependent on exposure contact time). Effects are immediate and delaye Symptoms may include irritation, Symptoms may include central neresulting in headache, nausea an May cause an allergic skin reaction. May cause drowsiness or dizzinear Review section 2 of SDS to see an antipatter of SDS to see antipatter of SDS to se	re (dose, concentration, ed. redness, pain, and rash. ervous system depression, d/or dizziness. on.
Notes to physician	: Treat symptomatically. Symptom	s may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SAFETY DATA SHEET MISTY DRY DEODORIZERS SPRING RAIN						
Version 2.2	Revision Date 09/17/2020	Print Date 03/20/2021				
Further information	: Collect contaminated fire exting must not be discharged into dra Standard procedure for chemica Fire residues and contaminated be disposed of in accordance w	ins. al fires. fire extinguishing water must				
Special protective equipment for firefighters	: Wear self-contained breathing a necessary.	apparatus for firefighting if				

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	:	Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Conditions for safe storage	:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a cool, well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	:	Oxidizing agents

Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
		STEL	750 ppm 1,780 mg/m3	CAL PEL
		С	3,000 ppm	CAL PEL
		PEL	500 ppm 1,200 mg/m3	CAL PEL
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-PROPANONE	67-64-1	Acetone	Urine	End of	25 mg/l	ACGIH BEI
				shift (As	-	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Version 2.2	Revision Date 09/17/2020	Print Date 03/20/2021
Respiratory protection	: No personal respiratory protective e required.	equipment normally
Hand protection Remarks	: The use of skin protection is not no good industrial hygiene practice su other appropriate skin protection when	ggests the use of gloves or nenever working with
Eye protection	 chemicals, and especially if prolong possible or likely. Always wear eye protection when the eye contact with the product cannot 	ne potential for inadvertent
Skin and body protection	: No special protection is required.	
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at t	he end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	colourless
Odour	:	odourized
Odour Threshold	:	No data available
рН	:	No data available
Melting point/freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas, liquid)	:	Extremely flammable aerosol.
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	< 1 g/cm3
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	not determined
Partition coefficient: n-	:	No data available

Version 2.2	Revision Date 09/17/2020	Print Date 03/20/2021	
octanol/water			
Auto-ignition temperature	: not determined		
Thermal decomposition	: No data available		
Viscosity			
Viscosity, kinematic	: No data available		
Heat of combustion	: 34.80 kJ/g		

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Chronic effects are delayed and symptoms may not be observed during an exposure. Effects are dependent on exposure (dose, concentration, contact time). Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms may include central nervous system depression, resulting in headache, nausea and/or dizziness. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Version 2.2	Revision Date 09/17/2020	Print Date 03/20/202
Carcinogenicity:		
IARC ACGIH	No component of this product preser equal to 0.1% is identified as probab human carcinogen by IARC.	le, possible or confirmed
ACGIN	No component of this product preser equal to 0.1% is identified as a carcin carcinogen by ACGIH.	
OSHA	No component of this product preser equal to 0.1% is on OSHA's list of re	
NTP	No component of this product preser equal to 0.1% is identified as a know by NTP.	nt at levels greater than or
Acute toxicity		
Components:		
acetone:		
Acute oral toxicity	: LD50 Rat: 5,800 mg/kg	
Acute inhalation toxicity	: LC50 Rat: 132 mg/l	
	Exposure time: 3 h	
	LC50 Rat: 50.1 mg/l	
Acute dermal toxicity	: LD50 Guinea pig: > 7,426 mg/kg	
	LD50 Rabbit: > 7,426 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: May irritate skin.		
Serious eye damage/eye irritati	on	
Product:		
Remarks: Eye irritation		
Respiratory or skin sensitisatio	n	
Product:		
Remarks: Causes sensitisation	on.	
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		

Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available Bioaccumulative potential

Product:

Partition coefficient: n- octanol/water <u>Components:</u> butane :	
Partition coefficient: n- octanol/water	: Pow: 2.89
Mobility in soil	
No data available	
Other adverse effects	
No data available Product:	
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological	: No data available

Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

information

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

Version 2.2

Print Date 03/20/2021

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
hydroquinone	123-31-9	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards	Flammable (gases, aerosols, liquids, or solids) Gases under pressure Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposu	re)
SARA 302	lo chemicals in this material are subject to the reporting equirements of SARA Title III, Section 302.	3
SARA 313	This material does not contain any chemical component nown CAS numbers that exceed the threshold (De Min eporting levels established by SARA Title III, Section 3	nimis)
California Prop. 65		
	This product contains a chemical that is at or below C Propositions 65's "safe harbor level" for carcinogenicit determined via a risk assessment. Therefore, the cher not required to be listed as a Prop 65 chemical on the	ty as mical is

The components of this product are reported in the following inventories:

label.

DSL	This product contains one or more components that are listed on the
	Canadian NDSL. All other components are on the Canadian DSL.
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

Further information

NFPA:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High


4 = Extreme

HMIS III:

HEALTH	3*
FLAMMABILITY	4
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High
- 4 = Extreme, * = Chronic



Version 2.2

Revision Date 09/17/2020

Print Date 03/20/2021

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	2.2
Revision Date:	09/17/2020
Print Date:	03/20/2021

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.