



LPS MAX 2™

Lubricant, Penetrant & Protectant



FEATURES

- Superior penetration and up to 1 year indoor parts protection
- 24.8% more penetration
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip
- Locking flip straw actuator

APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Hand Tools
- Dies, Bits & Fasteners
- Slides & Tracks
- Production & Transportation Equipment
- Metal Parts in Storage
- Pulleys & Rollers
- Engines & Electric Motors

SPECIFICATIONS AND APPROVALS

- NSF International: H2

PROPERTIES

Appearance / Physical State	Gas
Color	Brown
Odor	Slight petroleum odor. Cherry.
Melting / Freezing Point	< -58°F (< -50°C)
Flash Point	174.2°F (79.0°C) Tag Closed Cup (dispensed liquid)
Evaporation Rate	> 0.1 BuAc
Flammability	Flammable gas
Vapor Pressure	< 0.05 mm Hg @ 20°C (dispensed liquid)
Vapor Density	4.7 (air = 1)
Partition Coefficient	< 1
Auto-Ignition Temperature	> 442.2°F (>228°C)
Viscosity	< 7 cSt
Explosive Properties	None
Heat of Combustion	> 30 kJ/g
Oxidizing Properties	None
Percent Volatile	92-95%
Specific Gravity	0.82-0.86 @ 20°C
Prop 65 Warning	Yes

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
90216	11 wt oz / 312 g / 369 mL	aerosol	12	11 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved