

# GTA056\_A2

## Safety Data Sheet INTERNATIONAL THINNER (GTA056 / T-9)



Bulk Sales Reference No.:  
SDS Revision Date:  
SDS Revision Number:

Sales  
Order: {SalesOrd}  
GTA056  
10/06/2016  
A2-3

### 1. Identification of the preparation and company

#### 1.1. Product identifier

Product Identity INTERNATIONAL THINNER (GTA056 / T-9)  
Bulk Sales Reference No. GTA056

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.  
Application Method See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC  
6001 Antoine Drive  
Houston Texas 77091

#### Emergency

CHEMTREC (USA) (800) 424-9300  
International Paint (713) 682-1711  
Poison Control Center (800) 854-6813  
Customer Service  
International Paint (800) 589-1267  
Fax No. (800) 631-7481

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.  
Skin Irrit. 2;H315 Causes skin irritation.  
Eye Irrit. 2;H319 Causes serious eye irritation.  
STOT SE 3;H336 May cause drowsiness or dizziness.  
Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Warning.

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P331 Do NOT induce vomiting.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P391 Collect spillage.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating                      Health: 2                      Flammability: 2                      Reactivity: 0

|   |
|---|
| 3. Composition/information on ingredients |
|---|

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations                         | Weight % | GHS Classification   | Notes  |
|--|----------|--|--------|
| BUTYL ACETATE<br>CAS Number: 0000123-86-4                | 25 - 50  | Flam. Liq. 3;H226<br>STOT SE 3;H336  | [1][2] |
| Petroleum naphtha<br>CAS Number: 0064742-95-6            | 25 - 50  | Asp. Tox. 1;H304<br>Aquatic Chronic 2;H411 (Self Classification)   | [1]    |
| 1,2,4-Trimethyl benzene<br>CAS Number: 0000095-63-6      | 10 - 25  | Flam. Liq. 3;H226<br>Acute Tox. 4;H332<br>Eye Irrit. 2;H319<br>STOT SE 3;H335<br>Skin Irrit. 2;H315<br>Aquatic Chronic 2;H411                | [1]    |
| Methyl n-amyl ketone<br>CAS Number: 0000110-43-0         | 10 - 25  | Flam. Liq. 3;H226<br>Acute Tox. 4;H332<br>Acute Tox. 4;H302  | [1][2] |
| 1,3,5-Trimethylbenzene<br>CAS Number: 0000108-67-8       | 1.0 - 10 | Flam. Liq. 3;H226<br>STOT SE 3;H335<br>Aquatic Chronic 2;H411  | [1]    |
| Xylenes (o-, m-, p- isomers)<br>CAS Number: 0001330-20-7 | 1.0 - 10 | Flam. Liq. 3;H226<br>Acute Tox. 4;H332<br>Acute Tox. 4;H312<br>Skin Irrit. 2;H315<br>Eye Irrit. 2;H319<br>STOT SE 3;H335<br>Asp. Tox. 1;H304 | [1][2] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

|                       |
|-----------------------|
| 4. First aid measures |
|-----------------------|

## 4.1. Description of first aid measures

|            |   |
|------------|---|
| General    | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.  |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.  |
| Eyes       | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.   |
| Skin       | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.  |
| Ingestion  | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |

## 4.2. Most important symptoms and effects, both acute and delayed

|                 |   |
|-----------------|---|
| Overview        | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.                            |
| Inhalation      | Harmful if inhaled. May cause allergic respiratory reaction. May cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath and dry cough. May cause asthma-like symptoms to occur. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes            | Causes severe eye irritation. Avoid contact with eyes.  |
| Skin            | Causes skin irritation. May be harmful if absorbed through the skin.  |
| Ingestion       | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.  |
| Chronic effects |   |

|                           |
|---------------------------|
| 5. Fire-fighting measures |
|---------------------------|

## 5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

## 5.2. Special hazards arising from the substance or mixture

FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

## 5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 127

|                                |
|--------------------------------|
| 6. Accidental release measures |
|--------------------------------|

## 6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

## 6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

## 6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep

## GTA056\_A2

out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

### 7. Handling and storage

#### 7.1. Precautions for safe handling

##### Handling

Vapors may cause flash fire or ignite explosively.

##### In Storage

Keep away from heat, sparks and flame.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

#### 7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

| CAS No.      | Ingredient              | Source    | Value   |
|--------------|-------------------------|-----------|---|
| 0000095-63-6 | 1,2,4-Trimethyl benzene | OSHA      |   |
|              |                         | ACGIH     |   |
|              |                         | NIOSH     | 25 ppm TWA; 125 mg/m3 TWA   |
|              |                         | Supplier  |   |
|              |                         | OHSA, CAN |   |
|              |                         | Mexico    |   |
|              |                         | Brazil    |   |
| 0000108-67-8 | 1,3,5-Trimethylbenzene  | OSHA      |   |
|              |                         | ACGIH     |   |
|              |                         | NIOSH     | 25 ppm TWA; 125 mg/m3 TWA   |
|              |                         | Supplier  |   |
|              |                         | OHSA, CAN |   |
|              |                         | Mexico    |   |
|              |                         | Brazil    |   |
| 0000110-43-0 | Methyl n-amyl ketone    | OSHA      | 100 ppm TWA; 465 mg/m3 TWA  |
|              |                         | ACGIH     | 50 ppm TWA  |
|              |                         | NIOSH     | 100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH  |
|              |                         | Supplier  |   |
|              |                         | OHSA, CAN | 25 ppm TWA; 115 mg/m3 TWA   |
|              |                         | Mexico    | 50 ppm TWA LMPE-PPT; 235 mg/m3 TWA LMPE-PPT100 ppm STEL [LMPE-CT]; 465 mg/m3 STEL [LMPE-CT] |
|              |                         | Brazil    |   |
| 0000123-86-4 | BUTYL ACETATE           | OSHA      | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL                                      |
|              |                         | ACGIH     | 150 ppm TWA200 ppm STEL   |

## GTA056\_A2

|              |                              |           |  |
|--------------|------------------------------|-----------|--|
|              |                              | NIOSH     | 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700 ppm IDLH (10% LEL)                |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN | 150 ppm TWA200 ppm STEL  |
|              |                              | Mexico    | 150 ppm TWA LMPE-PPT; 710 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 950 mg/m3 STEL [LMPE-CT] |
|              |                              | Brazil    |  |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | OSHA      | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL                                       |
|              |                              | ACGIH     | 100 ppm TWA150 ppm STEL  |
|              |                              | NIOSH     |  |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN | 100 ppm TWA150 ppm STEL  |
|              |                              | Mexico    | 100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT] |
| 0064742-95-6 | Petroleum naphtha            | Brazil    | 78 ppm TWA LT; 340 mg/m3 TWA LT  |
|              |                              | OSHA      |  |
|              |                              | ACGIH     |  |
|              |                              | NIOSH     |  |
|              |                              | Supplier  |  |
|              |                              | OHSA, CAN |  |
|              |                              | Mexico    |  |
|              |                              | Brazil    |  |

## Health Data

| CAS No.      | Ingredient                   | Source | Value   |
|--------------|------------------------------|--------|---|
| 0000095-63-6 | 1,2,4-Trimethyl benzene      | NIOSH  |   |
| 0000108-67-8 | 1,3,5-Trimethylbenzene       | NIOSH  |   |
| 0000110-43-0 | Methyl n-amyl ketone         | NIOSH  | Irritation; liver kidney  |
| 0000123-86-4 | BUTYL ACETATE                | NIOSH  | Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals |
| 0001330-20-7 | Xylenes (o-, m-, p- isomers) | NIOSH  | Central nervous system depressant; respiratory and eye irritation                               |
| 0064742-95-6 | Petroleum naphtha            | NIOSH  |   |

## Carcinogen Data

| CAS No.      | Ingredient              | Source | Value  |
|--------------|-------------------------|--------|--|
| 0000095-63-6 | 1,2,4-Trimethyl benzene | OSHA   | Select Carcinogen: No  |
|              |                         | NTP    | Known: No; Suspected: No   |
|              |                         | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-67-8 | 1,3,5-Trimethylbenzene  | OSHA   | Select Carcinogen: No  |
|              |                         | NTP    | Known: No; Suspected: No   |
|              |                         | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000110-43-0 | Methyl n-amyl ketone    | OSHA   | Select Carcinogen: No  |
|              |                         | NTP    | Known: No; Suspected: No   |
|              |                         | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000123-86-4 | BUTYL ACETATE           | OSHA   | Select Carcinogen: No  |
|              |                         | NTP    | Known: No; Suspected: No   |
|              |                         | IARC   | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0001330-20-7 |                         | OSHA   | Select Carcinogen: No  |

## GTA056\_A2

|              |                             |      |   |
|--------------|-----------------------------|------|---|
|              | Xylenes (o-, m-, p-isomers) | NTP  | Known: No; Suspected: No  |
|              |                             | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0064742-95-6 | Petroleum naphtha           | OSHA | Select Carcinogen: No   |
|              |                             | NTP  | Known: No; Suspected: No  |
|              |                             | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;  |

## 8.2. Exposure controls

|                      |   |
|----------------------|---|
| Respiratory          | Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
| Eyes                 | Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.  |
| Skin                 | Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.   |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation.   |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.  |

## 9. Physical and chemical properties

|   |  |
|---|--|
| Appearance                                      | Coloured Liquid  |
| Odour threshold                                 | Not Measured   |
| pH  | No Established Limit   |
| Melting point / freezing point                  | Not Measured   |
| Initial boiling point and boiling range         | 125 (°C) 257 (°F)  |
| Flash Point                                     | 36 (°C) 96 (°F)  |
| Evaporation rate (Ether = 1)                    | Not Measured   |
| Flammability (solid, gas)                       | Not Applicable   |
| Upper/lower flammability or explosive limits    | Lower Explosive Limit: 1<br>Upper Explosive Limit: No Established Limit    |
| vapor pressure (Pa)                             | Not Measured   |
| Vapor Density                                   | Heavier than air   |
| Specific Gravity                                | 0.87   |
| Solubility in Water                             | Not Measured   |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured   |
| Auto-ignition temperature                       | Not Measured   |
| Decomposition temperature                       | Not Measured   |
| Viscosity (cSt)                                 | No Established Limit Not Measured  |
| VOC %   | Refer to the Technical Data Sheet or label where information is available. |

## 10. Stability and reactivity

## 10.1. Reactivity

No data available

## 10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

## 10.3. Possibility of hazardous reactions

No data available

## 10.4. Conditions to avoid

No data available

## 10.5. Incompatible materials

Strong oxidizing agents.

## 10.6. Hazardous decomposition products

FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated.

## 11. Toxicological information

## Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient                                 | Oral LD50,<br>mg/kg           | Skin LD50,<br>mg/kg              | Inhalation<br>Vapor LD50,<br>mg/L/4hr | Inhalation<br>Dust/Mist LD50,<br>mg/L/4hr |
|--|-------------------------------|----------------------------------|---------------------------------------|---|
| BUTYL ACETATE - (123-86-4)                 | 10,700.00, Rat - Category: NA | 17,600.00, Rabbit - Category: NA | No data available                     | No data available                         |
| Petroleum naphtha - (64742-95-6)           | 6,800.00, Rat - Category: NA  | 3,400.00, Rabbit - Category: 5   | No data available                     | No data available                         |
| 1,2,4-Trimethyl benzene - (95-63-6)        | 3,400.00, Rat - Category: 5   | 3,160.00, Rabbit - Category: 5   | 18.00, Rat - Category: 4              | No data available                         |
| Methyl n-amyl ketone - (110-43-0)          | 1,670.00, Rat - Category: 4   | 12,600.00, Rabbit - Category: NA | No data available                     | No data available                         |
| 1,3,5-Trimethylbenzene - (108-67-8)        | No data available             | No data available                | 24.00, Rat - Category: NA             | No data available                         |
| Xylenes (o-, m-, p- isomers) - (1330-20-7) | 4,299.00, Rat - Category: 5   | 1,548.00, Rabbit - Category: 4   | 20.00, Rat - Category: 4              | No data available                         |

| Item  | Category       | Hazard                             |
|---|----------------|------------------------------------|
| Acute Toxicity (mouth)                                    | Not Classified | Not Applicable                     |
| Acute Toxicity (skin)                                     | Not Classified | Not Applicable                     |
| Acute Toxicity (inhalation)                               | Not Classified | Not Applicable                     |
| Skin corrosion/irritation                                 | 2              | Causes skin irritation.            |
| Eye damage/irritation                                     | 2              | Causes serious eye irritation.     |
| Sensitization (respiratory)                               | Not Classified | Not Applicable                     |
| Sensitization (skin)                                      | Not Classified | Not Applicable                     |
| Germ toxicity   | Not Classified | Not Applicable                     |
| Carcinogenicity   | Not Classified | Not Applicable                     |
| Reproductive Toxicity                                     | Not Classified | Not Applicable                     |
| Specific target organ systemic toxicity (single exposure) | 3              | May cause drowsiness or dizziness. |

## GTA056\_A2

|   |                |                |
|---|----------------|----------------|
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard   | Not Classified | Not Applicable |

## 12. Ecological information

## 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

## Aquatic Ecotoxicity

| Ingredient                                 | 96 hr LC50 fish, mg/l       | 48 hr EC50 crustacea, mg/l | ErC50 algae, mg/l                        |
|--|-----------------------------|----------------------------|--|
| BUTYL ACETATE - (123-86-4)                 | 18.00, Pimephales promelas  | 32.00, Artemia salina      | 674.70 (72 hr), Scenedesmus subspicatus  |
| Petroleum naphtha - (64742-95-6)           | 9.22, Oncorhynchus mykiss   | 6.14, Daphnia magna        | 19.00 (72 hr), Selenastrum capricornutum |
| 1,2,4-Trimethyl benzene - (95-63-6)        | 7.72, Pimephales promelas   | 3.60, Daphnia magna        | Not Available                            |
| Methyl n-amyl ketone - (110-43-0)          | 131.00, Pimephales promelas | Not Available              | Not Available                            |
| 1,3,5-Trimethylbenzene - (108-67-8)        | 12.52, Carassius auratus    | 6.00, Daphnia magna        | 25.00 (48 hr), Scenedesmus subspicatus   |
| Xylenes (o-, m-, p- isomers) - (1330-20-7) | 3.30, Oncorhynchus mykiss   | 8.50, Palaemonetes pugio   | 100.00 (72 hr), Chlorococcales           |

## 12.2. Persistence and degradability

No data available

## 12.3. Bioaccumulative potential

Not Measured

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

## 12.6. Other adverse effects

No data available

## 13. Disposal considerations

## 13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

## 14. Transport information

## 14.1. UN number

UN 1263

## 14.2. UN proper shipping name

PAINT RELATED MATERIAL

## 14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name PAINT RELATED MATERIAL

DOT Hazard Class 3 - Flammable

IMO / IMDG (Ocean Transportation)

IMDG Proper Shipping Name PAINT RELATED MATERIAL



## GTA056\_A2

UN / NA Number UN 1263  
 DOT Packing Group III  
 CERCLA/DOT RQ 840 gal. / 6061 lbs.

IMDG Hazard Class 3 - Flammable  
 Sub Class 3 - Flammable

IMDG Packing Group III  
 System Reference 30  
 Code

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No ( Petroleum naphtha )

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

### 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2B

DOT Marine Pollutants (10%):  
 (No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):  
 (No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

Cumene (5000 lb final RQ; 2270 kg final RQ)

BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :  
 (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-Trimethyl benzene

Cumene

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

1,2,4-Trimethyl benzene

Methyl n-amyl ketone

BUTYL ACETATE

1,3,5-Trimethylbenzene

Xylenes (o-, m-, p- isomers)

Penn RTK Substances (>1%) :

1,2,4-Trimethyl benzene

Methyl n-amyl ketone

BUTYL ACETATE

Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :  
 (No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

1,2,4-Trimethyl benzene

Methyl n-amyl ketone

BUTYL ACETATE

Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

Cumene

BUTYL ACETATE

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene

Cumene

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Cumene

Proposition 65 - Female Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):

(No Product Ingredients Listed)

|                       |
|-----------------------|
| 16. Other information |
|-----------------------|

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

End of Document