

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS #: 082987

Revision Date: 2015-10-13 Date of the previous version: 2015-04-02 Version 1.01

AZOLLA ZS 46

1. IDENTIFICATION

Product identifier

Product name AZOLLA ZS 46

Other means of identification

082987 Product Code(s)

Number 161 Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Hydraulic oil.

Do not use for any purpose other than the one for which it is intended Uses advised against

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc

1201 Louisiana Street, Suite 1800

Houston, TX 77002 Phone: +1 800 323 3198

Technical/ HSEQ **Contact Point**

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number +1 (908) 862-9300

Emergency telephone CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Unknown Acute Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity***

Hazards not otherwise classified (HNOC)

None known

Other information

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental properties Should not be released into the environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Distillates (petroleum), hydrotreated heavy	64742-54-7	50-55
paraffinic		

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

* The exact percentage (concentration) of composition has been withheld as a trade secret***

4. FIRST AID MEASURES

First aid measures for different exposure routes

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Rinse immediately with plenty of water and seek medical advice.

Skin contact Remove contaminated clothing and shoes. Wash off with soap and water. Wash

contaminated clothing before reuse.

Inhalation Move to fresh air. Inhalation of high concentrations of vapor or aerosols may cause irritation

of the upper respiratory tract.

Ingestion If swallowed, do not induce vomiting - seek medical advice.

Most important symptoms/effects, acute and delayed

Skin contactNot classified. High pressure injection of the products under the skin may have very serious

consequences even though no symptom or injury may be apparent.

Eye contact Not classified. May cause eye irritation with susceptible persons.



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Symptoms Redness. Itching.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Foam. Carbon dioxide (CO₂). ABC powder. Water spray.

Unsuitable Extinguishing MediaDo not use a solid water stream as it may scatter and spread fire.

<u>Special Hazard</u> Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

Explosion Data

Sensitivity to Mechanical Impact

Sensitivity to Static Discharge

None. None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Try to prevent the material from

entering drains or water courses. Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g.

sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for

disposal.



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in

well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes

and clothing.

Prevention of fire and explosion Take precautionary measures against static discharges. Ground/bond containers, tanks

and transfer/receiving equipment.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Protect from frost, heat and sunlight. Protect from moisture. Design equipment to avoid accidental product leakage (for example due to seal failure) onto hot casings or electrical contacts.

Materials to Avoid Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH

(TLV) TWA 5 mg/m³ (highly refined).

Exposure controls

Engineering Measures Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

General Information If the product is used in mixtures, it is recommended that you contact the appropriate

protective equipment suppliers. These recommendations apply to the product as supplied.



Date of the previous version: 2015-04-02 **Revision Date: 2015-10-13** Version 1.01

Eye/Face Protection If splashes are likely to occur, wear:. Safety glasses with side-shields.

Skin and body protection Wear suitable protective clothing. Protective shoes or boots.

Hand Protection Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. Please observe the

> instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which

the product is used, such as the danger of cuts, abrasion, and the contact time.

None required under normal usage. If exposure limits are exceeded or irritation is Respiratory protection

experienced, NIOSH/MSHA approved respiratory protection should be worn.

Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local

regulations.

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of Hygiene measures

contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do

not use abrasives, solvents or fuels. Do not dry hands with rags that have been

contaminated with product. Do not put product contaminated rags into workwear pockets.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Color amber Physical State @20°C liauid

Odor Petroleum distillates

Odor Threshold No information available

Method **Property** <u>Values</u> Remarks

Not applicable На

Melting point/range No information available

Not applicable Boiling point/boiling range

Flash point 210 °C Cleveland Open Cup (COC)

ASTM D 92

410 °F Cleveland Open Cup (COC).

ASTM D 92.

Evaporation rate

No information available No information available Flammability Limits in Air upper No information available Lower No information available No information available **Vapor Pressure**

Vapor density No information available

Relative density 0.872 @ 15 °C **ASTM D 1298**



Date of the previous version: 2015-04-02 **Revision Date: 2015-10-13** Version 1.01

872 kg/m3 @ 15 °C Density **ASTM D 1298** Not applicable

Water solubility

Solubility in other solvents

logPow

Autoignition temperature

Decomposition temperature

Viscosity, kinematic **Explosive properties**

Oxidizing Properties Possibility of hazardous reactions

Other information

Specific Gravity Freezing Point

0.872

46 mm2/s

Not explosive

Not applicable

Not applicable

@ 15 °C

No information available

No information available

No information available

No information available

Not applicable

@ 40 °C

-29 °C Pour point

ASTM D 1298

ASTM D 445

ASTM D 97

10. STABILITY AND REACTIVITY

Reactivity

Stable under recommended storage conditions. **Chemical stability**

Possibility of hazardous reactions None under normal processing.

Heat, flames and sparks. Take precautionary measures against static discharges. Heat **Conditions to Avoid**

(temperatures above flash point), sparks, ignition points, flames, static electricity. Strong

oxidizing agents.

Incompatible Materials Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Information on likely routes of exposure

Principle Routes of Exposure Inhalation, Ingestion, Eye contact, Skin contact.

Numerical measures of toxicity

5057 mg/kg ATEmix (oral) **ATEmix (dermal)** 5057 mg/kg

Inhalation

5.2 mg/l ATEmix (inhalation-dust/mist) ATEmix (inhalation-vapor) 30.3 mg/l



SDS #: 082987

AZOLLA ZS 46

Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated	LD50 > 5000 mg/kg bw (rat - OECD	LD50 > 5000 mg/kg bw (rabbit -	LC50 (4h) > 5 mg/l (aerosol) (rat -
heavy paraffinic	420)	OECD 402)	OECD 403)
64742-54-7	·		·

Information on toxicological effects

Symptoms Redness. Itching.

Skin contact Not classified. High pressure injection of the products under the skin may have very serious

consequences even though no symptom or injury may be apparent.

Eye contact Not classified. May cause eye irritation with susceptible persons.

Inhalation Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory

system.

Ingestion Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Not classified as a sensitizer.

Carcinogenicity This product is not classified carcinogenic.

Chemical Name	ACGIH	IARC	NTP	OSHA
Distillates (petroleum),	-	-		-
hydrotreated heavy				
paraffinic				
64742-54-7				

Mutagenicity Contains no ingredient listed as a mutagen.

Reproductive toxicity

Other adverse effects

This product does not present any known or suspected reproductive hazards.

Characteristic skin lesions (pimples) may develop following prolonged and repeated

exposures (contact with contaminated clothing).

Aspiration Hazard Not classified.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Acute aquatic toxicity - Product Information

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and	Toxicity to
			other aquatic invertebrates	microorganisms



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	, ,	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	
--	-----	--	--	--

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and	Toxicity to fish	Toxicity to
		other aquatic invertebrates		microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms No experimental data available .

Persistence and degradability

General Information No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

Chemical Name	log Pow		
Distillates (petroleum), hydrotreated heavy paraffinic	-		
64742-54-7			

Mobility

Soil No information available

Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories All the substances contained in this product are listed or exempted from listing in the

following inventories:

U.S.A. (TSCA)

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard no
Chronic Health Hazard no
Fire Hazard no
Sudden Release of Pressure Hazard no
Reactive Hazard no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).



SDS #: 082987

AZOLLA ZS 46

Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:***

Chemical Name	Weight %	California Prop. 65
Toluene - 108-88-3	<0.1	Developmental
		Female Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois
Paraffin oils (petroleum),catalytic dewaxed heavy 64742-70-7	Х			
Distillates (petroleum), hydrotreated light paraffinic 64742-55-8	X			

16. OTHER INFORMATION

NFPA Health Hazard 0 Flammability 1 Instability 0 Physical and chemical hazards -

HMIS Health Hazard 0 Flammability 1 Physical Hazard 0 Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-10-13

Revision Note *** Indicates updated section

Abbreviations, acronyms



Date of the previous version: 2015-04-02 Revision Date: 2015-10-13 Version 1.01

Legend Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the safety data sheet