

## **Features**

- Comes in sizes 36", 42", and 48"
  Rocker switch on 120V, Single Phase models
  SJT type 3 conductor, 12' long cord on 120V, Single Phase models / no cord on dual voltage models
- Aluminum, 4 paddle blade (48" PB / PBS have steel blade)
- Spiral, wire front and rear guards
- Corrosion and dent proof high density polyethylene housing
- 8" wheels (36" model), 10" wheels (42" & 48" models)
- Swivel model rotates 130° in 12 ½° increments and locks in place with a steel locking pin
- External junction boxes on dual voltage models allow units to be wired for either voltage without removing guards
- Hazardous location models have explosion proof motors. metal housings, and external junction boxes rated for Class I, Group D and Class II, Groups E, F, & G
- Meets OSHA standards
- 1 year limited warranty
- Made in U.S.A.



CORDWRAP INCLUDED WITH STANDARD MODEL

## Motor Specifications

- 1-Speed
- Permanently lubricated
- Ball bearing

## Standard Models

| MOTOR<br>LISTING       | SIZE | MOTOR                    |     |     |                     | CFM**  | VELOCITY<br>PROFILE      | STANDARD MODEL         |                 | SWIVEL MODEL             |                        |                 |     |
|------------------------|------|--------------------------|-----|-----|---------------------|--------|--------------------------|------------------------|-----------------|--------------------------|------------------------|-----------------|-----|
|                        |      | TYPE HP RPM AMPS         |     |     | CFM / Area<br>Sq Ft |        | MFG<br>CATALOG<br>NUMBER | MFG<br>MODEL<br>NUMBER | WT.<br>(LBS)    | MFG<br>CATALOG<br>NUMBER | MFG<br>MODEL<br>NUMBER | WT.<br>(LBS)    |     |
|                        |      | TYPE                     | нг  | KPM | AMPS                |        |                          | NUMBER                 | NOMBER          |                          | NUMBER                 | NUMBER          |     |
| c Usus Intertek        | 36"  | 120 V<br>1 PH<br>ODP     | 1/2 | 500 | 8.0                 | 6,900  | 14000 / 360              | 07964702               | PB 36-B         | 120                      | 07965002               | PBS 36-B        | 145 |
|                        | 42"  |                          | 3/4 | 430 | 11.0                | 10,600 | 17500 / 420              | 07964802               | PB 42-B         | 135                      | 07965102               | PBS 42-B        | 160 |
|                        | 48"  |                          | 1   | 390 | 15.0                | 14,400 | 23500 / 550              | 07964902               | PB 48-B         | 155                      | 07965202               | PBS 48-B        | 180 |
| c us serve us Intertek | 36"  | 240/480 V<br>3 PH<br>ODP | 1/2 | 500 | 2.3 /<br>1.1        | 6,900  | 14000 / 360              | 08508602               | PB 36-B-3       | 127                      | 08509202               | PBS 36-B-3      | 152 |
|                        | 42"  |                          | 3/4 | 430 | 3.3 /<br>1.5        | 10,600 | 17500 / 420              | 08508702               | PB 42-B-3       | 143                      | 08509302               | PBS 42-B-3      | 168 |
|                        | 48"  |                          | 1   | 390 | 3.4 /<br>1.7        | 14,400 | 23500 / 550              | 08508802               | PB 48-B-3       | 164                      | 08509402               | PBS 48-B-3      | 189 |
|                        | 36"  | 120/240 V<br>1 PH<br>EXP | 1/2 | 500 | 7.8 /<br>3.9        | 6,900  | 14000 / 360              | 08508902               | PB 36-B-<br>HL* | 135                      | 08509502               | PBS 36-B-<br>HL | 160 |
|                        | 42"  |                          | 3/4 | 430 | 10.8 /<br>5.4       | 10,600 | 17500 / 420              | 08509002               | PB 42-B-<br>HL* | 150                      | 08509602               | PBS 42-B-<br>HL | 175 |
|                        | 48"  |                          | 1   | 390 | 13.2 /<br>6.6       | 14,400 | 23500 / 550              | 08509102               | PB 48-B-<br>HL* | 173                      | 08509702               | PBS 48-B-<br>HL | 198 |

\*\*Measured 2 feet from face of fan \*Models have no listing. Note: Products listed in this section are custom built and subject to 100% cancellation/restocking charges. Note: Photograph is a representation of stocked models. Actual model may vary slightly in appearance