CRC.

SAFETY DATA SHEET

1. Identification

Product identifier SP-350™ Corrosion Inhibitor

Other means of identification

Product code 03266, 03268

Recommended use Lubricant and corrosion inhibitor

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical** 800-521-3168

Assistance

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1
Hazardous to the aquatic environment, acute Category 2

hazard

OSHA defined hazards Not classified.

Label elements

Environmental hazards





Signal word Danger

Hazard statement Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. Causes

serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use with adequate

ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash hands thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid release to the

environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as

this will spread the fire.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Material name: SP-350™ Corrosion Inhibitor
03266, 03268 Version #: 02 Revision date: 08-12-2015 Issue date: 11-01-2013

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national regulations.

None known.

3. Composition/information on ingredients

ixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	50 - 60
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	20 - 30
n-Butyl stearate		123-95-5	3 - 5
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3
Petrolatum		8009-03-8	1 - 3
Sodium petroleum sulfonate		68608-26-4	1 - 3
Solvent naphtha (petroleum), medium aliph.		64742-88-7	1 - 3
n-Nonane		111-84-2	< 0.3
n-Octane		111-65-9	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Water spray. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Water. Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

Material name: SP-350™ Corrosion Inhibitor

General fire hazards

SDS US 2 / 9

03266, 03268 Version #: 02 Revision date: 08-12-2015 Issue date: 11-01-2013

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep in an area equipped with sprinklers.

8. Exposure controls/personal protection

Occupational exposure limits U.S. - OSHA Components **Type** Value **Form** Fatty Acids, C18-unsatd., **TWA** 5 mg/m3 Respirable Dimers (CAS 61788-89-4) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Value **Form Type** Distillates (petroleum), PEL 5 mg/m3 Mist. solvent-refined heavy paraffinic (CAS 64741-88-4) 2000 mg/m3 500 ppm n-Octane (CAS 111-65-9) PEL 2350 mg/m3 500 ppm Petrolatum (CAS PEL 5 mg/m3 Mist. 8009-03-8) **ACGIH** Value **Form** Components **Type** Fatty Acids, C18-unsatd., 10 mg/m3 STEL Respirable Dimers (CAS 61788-89-4) **TWA** 5 mg/m3 Respirable **US. ACGIH Threshold Limit Values** Components Value **Form** Type Distillates (petroleum), **TWA** 5 mg/m3 Inhalable fraction. solvent-refined heavy paraffinic (CAS 64741-88-4)

Components	Туре	Value	Form
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
n-Nonane (CAS 111-84-2)	TWA	200 ppm	
n-Octane (CAS 111-65-9)	TWA	300 ppm	
Petrolatum (CAS 3009-03-8)	TWA	5 mg/m3	Inhalable fraction
Solvent naphtha petroleum), medium aliph. CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
JS. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Distillates (petroleum), nydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m3	
.,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
n-Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
-Octane (CAS 111-65-9)	Ceiling	1800 mg/m3 385 ppm	
	TWA	350 mg/m3	
		75 ppm	
Petrolatum (CAS 3009-03-8)	STEL	10 mg/m3	Mist.
•	TWA	5 mg/m3	Mist.
Solvent naphtha (petroleum), medium aliph. CAS 64742-88-7)	TWA	100 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Solvent naphtha (petroleum), medium aliph. (CAS

Can be absorbed through the skin.

64742-88-7)

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Neoprene.

Other Wear appropriate chemical resistant clothing.

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air monitoring is needed to determine

actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.

Form Liquid.

Color Yellow. Tan. Cream.

Odor Petroleum.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial bailing point and bailing \$200.00 ft.

Initial boiling point and boiling

range

> 392 °F (> 200 °C)

Flash point 190 °F (87.8 °C) Tag Closed Cup

Evaporation rate Slow.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit - upper

(%)

Not available.

Vapor pressure 0.6 hPa estimated

Vapor density > 1 (air = 1)

Relative density 0.86

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity (kinematic)

Percent volatile

Not available.

Not available.

80 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Sulfur compounds.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects. Expected to be a low hazard for

usual industrial or commercial handling by trained personnel.

Product Species Test Results

SP-350™ Corrosion Inhibitor

Acute Dermal

LD50 Rabbit 2089 mg/kg estimated

Oral

LD50 Rat 4732 mg/kg estimated

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eve irritation.

irritation

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not available.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. **Aspiration hazard**

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

toxicity	Toxic to a	quatic life.		
Product		Species	Test Results	
SP-350™ Corrosion In	hibitor			
Aquatic				
Crustacea	EC50	Daphnia	4419.04 mg/l, 48 hours estimated	
Acute				
Fish	LC50	Fish	4122.4038 ppm, 96 hours estimated	
Components		Species	Test Results	

Aquatic

Acute

03266, 03268

Fish LC50 Bluegill (Lepomis macrochirus) 2.2 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Partition coefficient n-octanol / water (log Kow)

Fatty Acids, C18-unsatd., Dimers 1 - 2.5, logKow

Version #: 02 Revision date: 08-12-2015 Issue date: 11-01-2013

n-Nonane 5.46 n-Octane 5.18

Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

^{*} Estimates for product may be based on additional component data not shown.

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Hazardous waste code

Not regulated.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - Yes

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely No hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)

Petrolatum (CAS 8009-03-8)

Material name: SP-350™ Corrosion Inhibitor

SDS US

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8) Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

US. Massachusetts RTK - Substance List

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

US. Pennsylvania Worker and Community Right-to-Know Law

1,2,4-Trimethylbenzene (CAS 95-63-6)

Distillates (petroleum), hydrotreated light (CAS 64742-47-8) Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

US. Rhode Island RTK

None.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 90.8 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

Inventory name

State

Consumer products

This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50

states.

 VOC content (CA)
 5.9 %

 VOC content (OTC)
 5.9 %

International Inventories

Country(s) or region

ountry (o) or region	mitorico, y mamo	• · · · · · · · · · · · · · · · · · · ·
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 11-01-2013
Revision date 08-12-2015
Prepared by Allison Cho
Version # 02

Further information CRC # 540F-G HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 0 Personal protection: B

Material name: SP-350™ Corrosion Inhibitor

SDS US

On inventory (yes/no)*

NFPA ratings

Health: 2 Flammability: 2 Instability: 0

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.