

# Material Safety Data Sheet



## 1. Chemical product and company identification

Product name	CASTROL DEXRON III / MERCON
MSDS #	452852
Historic MSDS #:	0000002669
Code	452852-US07, 10, 13, CA01
Product use	Automatic transmission fluid For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Manufacturer	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: (973) 633-2200 Telecopier: (973) 633-7475
EMERGENCY HEALTH INFORMATION:	1 (800) 447-8735 Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)
OTHER PRODUCT INFORMATION	1 (866) 4 BP - MSDS (866-427-6737 Toll Free - North America) email: bpcares@bp.com

## 2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Base oil - highly refined	64742-54-7	0 - 90
Base oil - highly refined	64741-89-5	0 - 90
Base oil - highly refined	64741-88-4 / 64741-89-5 / 64742-46-7 / 64742-54-7 / 64742-56-9 / 64742-65-0	5 - 10
Base oil - highly refined	72623-86-0	1 - 5

## 3. Hazards identification

Physical state	Liquid.
Color	Red. (Dark.)
Emergency overview	CAUTION!  MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION.  Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Routes of entry	Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects	

Product name CASTROL DEXRON III / MERCON

Product code 452852-US07, 10, 13, CA01

Page: 1/6

Version 2

Date of issue 08/11/2006.

Format US

Language ENGLISH.

Build 4.2.8

( ENGLISH )

<b>Eyes</b>	May cause eye irritation.
<b>Skin</b>	May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
<b>Inhalation</b>	May cause respiratory tract irritation.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation and diarrhea.
<b>Medical conditions aggravated by over-exposure</b>	None identified.
<b>See toxicological Information (section 11).</b>	

## 4. First aid measures

<b>Eye contact</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.
<b>Skin contact</b>	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.
<b>Inhalation</b>	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Ingestion</b>	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear. If large quantities of this material are swallowed, call a physician immediately.

## 5. Fire-fighting measures

<b>Flammability of the product</b>	May be combustible at high temperature.
<b>Flash point</b>	177 °C (Open cup) Cleveland.
<b>Products of combustion</b>	These products are carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide), nitrogen oxides (NO, NO <sub>2</sub> etc.), sulfur oxides (SO <sub>2</sub> , SO <sub>3</sub> etc.).
<b>Unusual fire/explosion hazards</b>	This material is not explosive as defined by established regulatory criteria.
<b>Fire-fighting media and instructions</b>	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide. Do not use water jet.
<b>Protective clothing (fire)</b>	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

## 6. Accidental release measures

<b>Personal precautions</b>	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
<b>Environmental precautions and clean-up methods</b>	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
<b>Personal protection in case of a large spill</b>	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

<b>Product name</b>	CASTROL DEXRON III / MERCON	<b>Product code</b>	452852-US07, 10, 13, CA01	<b>Page:</b> 2/6
<b>Version</b> 2	<b>Date of issue</b> 08/11/2006.	<b>Format</b> US	<b>Language</b> ENGLISH.	
	Build 4.2.8		( ENGLISH )	

## 7. Handling and storage

### Handling

Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Use only with adequate ventilation. Avoid breathing vapor or mist. Wash thoroughly after handling.

### Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### Ingredient name

#### Occupational exposure limits

Base oil - highly refined

##### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

##### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

##### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

##### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

##### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

##### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

Base oil - highly refined

##### ACGIH (United States).

STEL: 10 mg/m<sup>3</sup> 15 minute(s). Form: Oil mist, mineral

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

##### OSHA (United States).

TWA: 5 mg/m<sup>3</sup> 8 hour(s). Form: Oil mist, mineral

### Control Measures

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are close to the work-station location.

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

### Personal protection

#### Eyes

Avoid contact with eyes. Chemical splash goggles.

#### Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

#### Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

#### Hands

Wear suitable gloves.

Consult your supervisor or S.O.P. for special handling directions

Consult local authorities for acceptable exposure limits.

---

## 9. Physical and chemical properties

Physical state	Liquid.
Odor	Slight.
Color	Red. (Dark.)
Heat of combustion	Not available.
Specific gravity	0.86
Solubility	insoluble in water.
Viscosity	Kinematic: 30 to 40.1 mm <sup>2</sup> /s (30 to 40.1 cSt) at 40°C Kinematic: 6.8 to 9 mm <sup>2</sup> /s (6.8 to 9 cSt) at 100°C

---

## 10. Stability and reactivity

Stability and reactivity	The product is stable.
Conditions to avoid	Keep away from heat, sparks and flame.
Incompatibility with various substances	Reactive or incompatible with the following materials: oxidizing materials and reducing materials.
Hazardous decomposition products	Products of combustion: carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide), nitrogen oxides (NO, NO <sub>2</sub> etc.), sulfur oxides (SO <sub>2</sub> , SO <sub>3</sub> etc.).
Hazardous polymerization	Will not occur.

---

## 11. Toxicological information

### Chronic toxicity

#### Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

#### Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.

#### Reproductive effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.

#### Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

### Other chronic toxicity data

May cause sensitization by skin contact. May cause allergic reactions to certain individuals. Based on studies with similar substances.

---

## 12. Ecological information

Ecotoxicity	No testing has been performed by the manufacturer.
-------------	--

---

## 13. Disposal considerations

### Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

Consult your local or regional authorities.

---

## 14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

---

## 15. Regulatory information

### U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

TSCA 12(b) one-time export notification:: naphthalene

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: CASTROL DEXRON III / MERCON : Immediate (Acute) Health Hazard

### SARA 313

#### Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

#### Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Ethyl acrylate: 1000 lbs. (453.6 kg); naphthalene: 100 lbs. (45.36 kg);

### State regulations

Massachusetts RTK:Base oil - highly refined

**WARNING:** This product contains a chemical known to the State of California to cause cancer. Ethyl acrylate; naphthalene

### Inventories

AUSTRALIAN INVENTORY (AICS): In compliance.

CANADA INVENTORY (DSL): In compliance.

CHINA INVENTORY (IECS): In compliance.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (ENCS): In compliance.

KOREA INVENTORY (ECL): In compliance.

PHILIPPINE INVENTORY (PICCS): In compliance.

---

## 16. Other information

### Label requirements

CAUTION!

MAY CAUSE EYE IRRITATION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

**Product name** CASTROL DEXRON III / MERCON

**Product code** 452852-US07, 10, 13, CA01

**Page:** 5/6

**Version** 2

**Date of issue** 08/11/2006.

**Format** US

**Language** ENGLISH.

Build 4.2.8

( ENGLISH )

**HMIS® Rating :**

Health 1 -  
Flammability 1  
Physical Hazard 0  
Personal protection X

**National Fire  
Protection  
Association  
(U.S.A.)**

**History**

**Date of issue** 08/11/2006.  
**Date of previous issue** No Previous Validation.  
**Prepared by** Product Stewardship

**Notice to reader**

*NOTICE : This Material Safety Data Sheet is based upon data considered to be accurate at the time of its preparation. Despite our efforts, it may not be up to date or applicable to the circumstances of any particular case. We are not responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices or from hazards inherent in the nature of the product.*

**Product name** CASTROL DEXRON III / MERCON

**Product code** 452852-US07, 10, 13, CA01

**Page:** 6/6

**Version** 2 **Date of issue** 08/11/2006.

**Format** US

**Language** ENGLISH.

Build 4.2.8

( ENGLISH )