



QUIK-MARK™ WATER-BASED INVERTED MARKING

Quik-Mark™ Water-Based Inverted Marking Chalk is great for temporary markings on common outdoor surfaces. It is easily removed from hard surfaces with a wire brush and water. Our marking chalk formulation lasts 30 days or more, depending on conditions. Our marking chalk performance eliminates costly remarking, clogged and wasted cans, and allows marking with confidence in a variety of weather conditions. Selecting this high quality marking chalk will increase customer satisfaction while lowering overall costs.

- ✓ One pass valve for bold, bright, visible markings
- ✓ Glove Grip™ cap has a 50% wider opening to easily accommodate work gloves
- ✓ Spray-Thru™ cap – non-clogging spray tip
- ✓ Locking tip won't fall off with extended use
- ✓ Fast drying formula penetrates and adheres to hot, cold or wet surfaces
- ✓ VOC/MIR compliant

INDUSTRIAL USE ONLY!

krylonindustrial.com
1-800-247-3266

RECOMMENDED USES

- Road construction
- Concrete
- Asphalt
- Pavement
- Gravel
- Excavation
- Ground marking
- Surveying
- Construction marking
- Soil
- Grass
- Brick
- Utilities marking
- Communication lines
- Electrical installations
- Athletic fields

SURFACE PREPARATION

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. For more information, contact your local health authority. No surface preparation is necessary. Apply directly to desired surface.

CLEAN-UP

After Job Completion: Avoid clogging by turning can right-side up and spray until only clear gas appears. Wipe any paint off spray button opening.

TECHNICAL DATA

| | |
|---------------------------|---|
| Vehicle | Water reducible alkyd |
| Flash Point | -20°F |
| Weight/Gallon | 7.63 lb/gal |
| VOC/MIR | .33 |
| Spread Rate | 664 linear ft(1") for 17 oz. |
| Shelf life | 60 months |
| Drying Time | To Touch: >10 mins To Recoat > Anytime |
| Net Wt. / Can Size | 17 oz. / 20 oz. |

APPLICATION

APPLICATION CONDITIONS

For best results use when can is between 70-80°F. Shake can well until mixing ball breaks loose. Hold can at top and swing bottom of can in a circle until ball travels freely (repeat during extended use). To spray, invert can and point spray button 4-6 inches above surface. Press button to the side to actuate. Use with Krylon Marking Wands (K07095 and K07096) to reduce back strain and obtain consistent writing, stenciling and marking. When using marking wands, follow shaking instructions, then insert can and pull trigger to spray.

CAUTIONS

FOR INDUSTRIAL USE ONLY. Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

Note: The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.

The information and recommendations set forth in the Product Data Sheet are based upon tests conducted by or on behalf of Krylon® Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon® Industrial dealer or representative to obtain the most recent Product Data Sheet.