

Material Safety Data Sheet



Date of issue 18 February 2015

Version 24

1. Product and company identification

Product name : PSX 700 WHITE RESIN
Code : PX7003
Supplier : PPG Industries, Inc.
One PPG Place
Pittsburgh, PA 15272
Emergency telephone number : (412) 434-4515 (U.S.)
(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
Technical Phone Number : 888-977-4762

2. Hazards identification

Emergency overview : WARNING!
CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED OR SWALLOWED. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.
Do not swallow. Do not get on skin or clothing. Avoid breathing vapor or mist. Avoid contact with eyes. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation : May be harmful if inhaled. Irritating to respiratory system. Can irritate eyes, nose, mouth and throat. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion : May be harmful if swallowed.
Skin : Irritating to skin. May cause an allergic skin reaction.
Eyes : Irritating to eyes.

Over-exposure signs/symptoms

Trimethoxysilanes are capable of forming methanol if hydrolyzed or ingested. If swallowed, methanol may be harmful or fatal or cause blindness.

Medical conditions aggravated by over-exposure : Pre-existing skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS).

See toxicological information (Section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% (w/w)</u>
Proprietary silicone	Proprietary	15 - 40
titanium dioxide	13463-67-7	15 - 40
Epoxy	Not available.	10 - 30
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.5 - 1.5
silicon dioxide	7631-86-9	0.5 - 1.5
aluminium oxide	1344-28-1	0.5 - 1.5

3 . Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6 . Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not swallow. Do not get in eyes or on skin or clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Vapors are heavier than air and may spread along floors. Empty containers retain product residue and can be hazardous. Do not reuse container. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not store above the following temperature: 120F / 49C.

8 . Exposure controls/personal protection

Name	Result	ACGIH	Ontario	Mexico	PPG
Titanium dioxide	TWA	10 mg/m ³	10 mg/m ³ TD	10 mg/m ³ (as Ti)	Not established
	STEL	Not established	Not established	20 mg/m ³ (as Ti)	Not established
silicon dioxide	TWA	Not established	Not established	10 mg/m ³ 3 mg/m ³ R	Not established
aluminium oxide	TWA	3 mg/m ³ R 10 mg/m ³ 1 mg/m ³ R	10 mg/m ³ 10 mg/m ³ TD 10 mg/m ³ R 1 mg/m ³ R	10 mg/m ³	Not established

Key to abbreviations

A = Acceptable Maximum Peak	SR = Respiratory sensitization
ACGIH = American Conference of Governmental Industrial Hygienists.	SS = Skin sensitization
C = Ceiling Limit	STEL = Short term Exposure limit values
F = Fume	TD = Total dust
IPEL = Internal Permissible Exposure Limit	TLV = Threshold Limit Value
R = Respirable	TWA = Time Weighted Average
S = Potential skin absorption	

8 . Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Eyes** : Safety glasses with side shields.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Gloves** : butyl rubber
- Respiratory** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: 97.22°C (207°F)
- Explosion limits** : Lower: 1.5%
- Color** : Not available.
- Odor** : Not available.
- pH** : Not available.
- Boiling/condensation point** : >37.78°C (>100°F)
- Melting/freezing point** : Not available.
- Specific gravity** : 1.46
- Density (lbs / gal)** : 12.18
- Vapor pressure** : 1.6 kPa (12 mm Hg) [room temperature]
- Vapor density** : Not available.

9 . Physical and chemical properties

Volatility	: 0% (v/v), 0.17% (w/w)
Evaporation rate	: 0.7 (butyl acetate = 1)
Solubility	: Insoluble in the following materials: cold water.
Partition coefficient: n-octanol/water	: Not available.
% Solid. (w/w)	: 99.83

10 . Stability and reactivity

Stability	: The product may not be stable under certain conditions of storage or use.
Conditions to avoid	: Avoid increased storage temperature. Pressure hazard
Materials to avoid	: Reactive or incompatible with the following materials: acids, oxidizing materials, strong alkalis
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide	LD50 Oral	Rat	>10 g/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Target organs

: Contains material which causes damage to the following organs: upper respiratory tract, skin, eyes.
Contains material which may cause damage to the following organs: lungs, liver, central nervous system (CNS).

Carcinogenicity

Carcinogenicity : Contains material which may cause cancer, based on animal data. Risk of cancer depends on duration and level of exposure.

Classification

Product/ingredient name	ACGIH	IARC	NTP
Titanium dioxide	A4	2B	-
silicon dioxide	-	3	-
aluminium oxide	A4	-	-

Carcinogen Classification code: ACGIH: A1, A2, A3, A4, A5
IARC: 1, 2A, 2B, 3, 4
NTP: Known to be a human carcinogen; Reasonably anticipated to be a human carcinogen
Not listed or regulated as a carcinogen: -

12. Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 >100 mg/l Fresh water	Daphnia - Daphnia magna	48 hours

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	TDG	Mexico	IMDG
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)
Transport hazard class(es)	9	9	9
Packing group	III	III	III
Environmental hazards	Yes.	Yes.	Yes.
Marine pollutant substances	(Epoxy, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)	Not applicable.	(Epoxy, bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)

Additional information

TDG : The product is not regulated as a dangerous good when transported by road or rail.

Mexico : The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IMDG : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

14. Transport information

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.
Australia inventory (AICS) : All components are listed or exempted.
Canada inventory (DSL) : All components are listed or exempted.
China inventory (IECSC) : All components are listed or exempted.
Europe inventory (REACH) : Please contact your supplier for information on the inventory status of this material.
Japan inventory (ENCS) : All components are listed or exempted.
Korea inventory (KECI) : All components are listed or exempted.
New Zealand (NZIoC) : Not determined.
Philippines inventory (PICCS) : All components are listed or exempted.

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic). Class D-2B: Material causing other toxic effects (Toxic).

Mexico

Classification

Flammability : 1 **Health** : 2 **Reactivity** : 1

16. Other information

Hazardous Material Information System (U.S.A.)

Health : 2 * **Flammability** : 1 **Physical hazards** : 1

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 2 **Flammability** : 1 **Instability** : 1

Date of previous issue : 3/16/2014.

Organization that prepared the MSDS : EHS

✔ Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.