


Portable Surface Roughness Tester SURFTEST SJ-310 Series

Bulletin No. 2141



The Surftest SJ-310 is a compact, portable, easy-to-use surface roughness measurement instrument equipped with extensive measurement and analysis features.



Easy to use

Large color graphic LCD

The color touch-screen provides excellent readability and an intuitive display that is easy to negotiate. The LCD also includes a backlight for improved visibility in dark environments. The integrated printer allows you to print measurement results on the spot.

Highly functional

Internal memory

Up to 10 measurement conditions and one measured profile can be stored in the internal memory.

Optional memory card

The optional memory card can be used as an extended memory to store large quantities of measured profiles and conditions and adds the convenience of automatically saving data from the 10 most recent measurements (Trace 10).

Password protection

Access to each feature can be password-protected, which prevents unintended operations and allows protection of your settings.

Multilingual support

The display interface supports 16 languages, which can be freely switched.

Stylus alarm (patent pending in Japan, U.S.A., EU)

An alarm warns you when the cumulative measurement distance exceeds a preset limit.

Extensive analysis and display features

Complies with many industry standards

The Surftest SJ-310 complies with the following standards: JIS (JIS-B0601-2001, JIS-B0601-1994, JIS-B0601-1982), VDA, ISO-1997, and ANSI.

Displays assessed profiles and graphical data

In addition to calculation results, the Surftest SJ-310 can display sectional calculation results and assessed profiles, load curves, and amplitude distribution curves.

Enhanced power for making measurements on site

Despite its reduced charging time — approximately 1/4 that required for conventional models, the Surftest SJ-310 is capable of making approximately 2.5 times the number of measurements when fully charged. The detector supports a variety of measurement orientations and can make measurements up against a wall surface or while facing upward. When combined with optional accessories such as a height gauge adapter, the detector can make measurements in various orientations and settings.



Mitutoyo

Surftest SJ-310

User friendly, high-functionality display unit with integrated high-speed printer

The large 5.7-inch color graphic touch-screen LCD provides excellent readability. Furthermore, selecting icons from the touch panel display*1 provides intuitive and easy operation. The integrated high-speed printer also allows the user to perform the entire process from making measurements to printing the results with the push of a single button (START button). *1 Text display can also be selected.

Printer
BAC and ADC curves can be printed in addition to calculation results (including pass/fail results) and assessed profiles. The printer offers an easy-to-understand layout and can also print horizontally to match the content displayed on the LCD. Furthermore, printing speed is approximately 50% faster than conventional models.

5.7-inch color graphic LCD with touch screen
Measurement Result Measured profile ↔ One-touch switching BAC curve ADC curve

Key-sheet buttons
Frequently used functions, such as the measurement start button, are provided as rugged sheet buttons with excellent durability.

Built-in battery
With drastically enhanced power compared to conventional models, the Surftest SJ-310 can make 1,500 continuous measurements on a full charge achieved in 4 hours.


Highly functional detectors and drive units

Detector supplied as standard

One of two types may be selected:

- Measuring force: 0.75mN
Stylus form: Tip radius 2µm
Tip angle 60°
- Measuring force: 4mN
Stylus form: Tip radius 5µm
Tip angle 90°

A wide range of optional detectors is available, including detectors for small holes, extra small holes, gear tooth surfaces, and deep grooves.




Drive units

- Standard drive unit
• Popular standard drive unit
- Transverse tracing drive unit
• Best suited for measurement of narrow, shrouded workpiece features such as crankshaft bearings, EDM parts, etc. (Patent Registered in Japan)
- Retractable drive unit
• The detector is in the retracted position at rest so it is immune from damage when inserted into a feature whose shape cannot be easily seen, such as a blind hole, etc.



Links to a wide variety of external instruments


You can save parameter recalculations and measurement results in text format on a memory card and import into commercial spreadsheet software on a PC. You can also connect to a PC using the USB connector and use a dedicated software application to perform everything from measurement control and condition modification to issuing inspection result reports.




Measurement assistance and analysis features offering the ultimate in ease of use

Switches between icon and text display

The display can be switched between icon and text, providing easy, user-friendly operation. Additionally, the guidance feature provides detailed explanations of touch-screen buttons.



Icon



Text




Easy specification of assessment conditions from a list

Setting assessment conditions is simple because you can select the desired condition from a displayed list (e.g., standard, parameter).




Zooming waveforms and analyzing coordinate differences



You can not only magnify or shrink waveforms, but also calculate the coordinate difference between two points using a ruler operation. You can quickly check the irregularity status without waiting for a printout.

Deleting unnecessary data




With the Surftest SJ-310, you can delete portions of measurement data. This feature allows you to make new calculations by deleting data that should not be included in parameter calculation, such as data on a scratch.

Displaying pass/fail results


By specifying a tolerance in advance, you can display pass/fail results in color.



OK




+NG



-NG

Surface texture symbol entry

You can enter assessment conditions using ISO/JIS surface texture symbols. (Patent registered in Japan, U.S.A., Germany, UK, France) (Patent pending in China)



Specifications

Specifications

| Type of detector | Standard drive unit type | | Retractable drive unit type | | Transverse tracing drive unit | | |
|------------------------------|------------------------------------|--|-----------------------------|----------------------|--|----------------------------|--|
| Model No. | SJ-310 (0.75mN type) | SJ-310 (4mN type) | SJ-310 (0.75mN type) | SJ-310 (4mN type) | SJ-310 (0.75mN type) | SJ-310 (4mN type) | |
| Order No. | inch/mm | 178-571-01A | 178-571-02A | 178-573-01A | 178-573-02A | 178-575-01A 178-575-02A | |
| X axis | | .7" (17.5 mm) | | .22" (5.6 mm) | | | |
| Measuring range | Range | 14400 µinch (-7900 µinch to +6300 µinch) [360 µm (-200 µm ~ +160 µm)] | | | | | |
| Detector | Range/ resolution | 14400 µinch / .8 µinch (360 µm / 0.02 µm) | | | | | |
| | | 4000 µinch / .2 µinch (100 µm / 0.006 µm) | | | | | |
| | | 1000 µinch / .08 µinch (25 µm / 0.002 µm) | | | | | |
| Measuring speed | | In the measurement: .01inch/s (0.25mm/s), .02inch/s (0.5mm/s), .03inch/s (0.75mm/s), In the return: .04inch/s (1mm/s) | | | | | |
| Measuring force / Stylus tip | | 0.75mN type: 0.75mN / 2µmR 60°, 4mN type: 4mN / 5µmR 90° | | | | | |
| Skid force | | 400mN or less | | | | | |
| Standard | | JIS'82 / JIS'94 / JIS'01 / ISO'97 / ANSI / VDA / FREE | | | | | |
| Measured profiles | | Primary(P), Roughness(R), DF, R-Motif, W-Motif | | | | | |
| Parameters | | Ra, Rc, Ry, Rz, Rq, Rt, Rmax*1, Rp, Rv, R3z, Rsk, Rku, Rc, RPC, Rsm, Rz1max*2, S, HSC, RzJIS*3, Rppi, RΔa, RΔq, Rlr, Rmr, Rmr(c), Rδc, Rk, Rpk, Rvk, Mr1, Mr2, A1, A2, Vo, λa, λq, Lo, Rpm, tp*4, R, Rx, AR, W, AW, Wx, Wte, Possible Customize | | | | | |
| Graph analysis | | BAC and ADC curves | | | | | |
| Filter | | Gaussian, 2CR75, PC75 | | | | | |
| Cut-off length | $\frac{\lambda_c}{\lambda_s}^{*5}$ | .003, .01, .03, .1, .3" (0.08, 0.25, 0.8, 2.5, 8 mm) | | | | | |
| Sampling length | | 100, 320 µinch (2.5, 8 µm) | | | | | |
| Number of sampling lengths | | .003, .01, .03, .1, .3" (0.08, 0.25, 0.8, 2.5, 8 mm) | | | x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary .0118 ~ .6299" (.0001" Interval) [(0.3 ~ 16.0mm: 0.01mm Interval)] | | x1, x2, x3, x4, x5, x6, x7, x8, x9, x10, Arbitrary .0118 ~ .22" (.0001" Interval) [(0.3 ~ 5.6mm: 0.01mm Interval)] |
| LCD dimensions | | 4.64" x 3.47" (117.8 x 88.2 mm) | | | | | |
| Display languages | | Japanese, English, German, French, Italian, Spanish, Portuguese, Korean, Traditional Chinese, Simplified Chinese, Czech, Polish, Hungarian Turkish, Swedish, Dutch | | | | | |
| Measurement result display | | 1-parameter display: one parameter measurement result 4-parameter display: four parameter measurement results Profile display: one parameter measurement result and the measured profile Trace display: The ten latest measurement results using the same parameter | | | | | |
| Printing function | | Measurement conditions / Calculation results / GO / NG judgement result / Calculation results for each sampling length / Measurement curve / BAC / ADC / Environmental setting information | | | | | |
| External I/O | | USB I/F, Digimatic output, RS-232C I/F, External SW I/F | | | | | |
| Functions | Customization | Desired parameters can be selected for calculation and display | | | | | |
| | GO / NG judgement *6 | Max rule / 16% rule / Average rule / Standard deviation (1σ, 2σ, 3σ) | | | | | |
| | Storage of measurement condition | Save the condition at power OFF | | | | | |
| Storage | | Internal memory: Measurement condition (10 sets) Memory card (option): 500 measurement conditions, 1000 measuring data, 10000 text data, 500 statistic data, 500 image data, 1 backup of machine setting, the last ten traces (Trace 10) | | | | | |
| Calibration | | Saves last inputted nominal value of specimen / Average calibration with multiple measurement (MAX.12 times) is available | | | | | |
| Power-saving | | Auto-sleep function (30-600sec) *7 | | | | | |
| Power supply | | Two-way power supply: battery (rechargeable Ni-MH battery) and AC adapter *Charging time: about 4 hours (may vary due to ambient temperature) *Endurance: about 1500 measurements (differs slightly due to use conditions / environment) | | | | | |
| Size (WxDxH) | Display unit | 10.8" x 4.3" x 7.8" (275 x 109 x 198 mm) | | | | | |
| | Drive unit | 4.5" x 0.9" x 8.9" (115 x 23 x 26.7 mm) | | | | | |
| Mass | | About 1.8kg (Display unit + Drive unit + Standard detector) | | | | | |
| Standard accessories | | 12AAM475 Connecting cable *8 12AAA217 Nosepiece for plane surface 12AAA218 Nosepiece for cylinder 12AAA216 Supporting leg 12BAK700 Calibration stage 12BAG834 Stylus pen 12BAL402 Protection sheet 270732 Printer paper (5 pieces) 12BAL400 Carrying case | | | 12AAM475 Connecting cable *8 12AAE643 Point-contact adapter 12AAE644 V-type adapter 12BAK700 Calibration stage 12BAG834 Stylus pen 12BAL402 Protection sheet 270732 Printer paper (5 pieces) 12BAL400 Carrying case | | |
| | | Roughness reference specimen (Ra 3µm), AC adapter, Philips screwdriver, Strap for stylus pen, Operation manual, Quick reference manual, Warranty | | | | | Roughness reference specimen (Ra 1µm), AC adapter, Philips screwdriver, Strap for stylus pen, Operation manual, Quick reference manual, Warranty |

*1: Only for VDA/ANSI/JIS'82 standards.

*2: Only for JIS'97 standard.

*3: Only for JIS'01 standard.

*4: Only for ANSI standard.

*5: λs may not be switchable depending on a standard selected.

*6: Standard deviation only can be selected in ANSI.16% rule cannot be selected in VDA.

*7: Auto-sleep function is invalid when AC adapter is used.

*8: For connecting the calculation display unit and drive unit.


Dimensions: Display Unit and Drive Unit

Drive unit, Display unit

Unit: inch(mm)

| Drive unit type | Drive unit external view |
|-------------------------------|--------------------------|
| Standard drive unit | |
| Retractable drive unit | |
| Transverse tracing drive unit | |

Display unit external view




Dimensions: Detectors

Detectors

Unit: mm


Standard detectors



| Order No. | Measuring force | Stylus form* | Remarks |
|----------------|-----------------|--------------|--|
| 178-296 | 0.75mN | 2 μmR/60° | Dedicated to the standard/retractable drive unit |
| 178-390 | 4 mN | 5 μmR/90° | |
| 178-387 | 0.75mN | 2 μmR/60° | Dedicated to the transverse tracing drive unit |
| 178-386 | 4 mN | 5 μmR/90° | |
| 178-395 | 0.75mN | 2 μmR/90° | Dedicated to the standard/retractable drive unit |
| 178-391 | 4 mN | 10 μmR/90° | |

*Tip radius / Tip angle


Gear-tooth surface detectors



| Order No. | Measuring force | Stylus form* |
|----------------|-----------------|--------------|
| 178-388 | 0.75mN | 2 μmR/60° |
| 178-398 | 4 mN | 5 μmR/60° |

*Tip radius / Tip angle


Small hole detectors



| Order No. | Measuring force | Stylus form* | Remarks |
|----------------|-----------------|--------------|--|
| 178-383 | 0.75mN | 2 μmR/60° | Minimum measurable hole diameter: φ4.5mm |
| 178-392 | 4 mN | 5 μmR/90° | |

*Tip radius / Tip angle


Deep groove detectors



| Order No. | Measuring force | Stylus form* | Remarks |
|----------------|-----------------|--------------|---|
| 178-385 | 0.75mN | 2 μmR/60° | Not available for the transverse tracing drive unit |
| 178-394 | 4 mN | 5 μmR/90° | |

*Tip radius / Tip angle

Extra small hole detectors



| Order No. | Measuring force | Stylus form* | Remarks |
|----------------|-----------------|--------------|--|
| 178-384 | 0.75mN | 2 μmR/60° | Minimum measurable hole diameter: φ2.8mm |
| 178-393 | 4 mN | 5 μmR/90° | |

*Tip radius / Tip angle



Dimensions: Display Unit and Drive Unit

Drive unit, Display unit

Nosepiece for flat surfaces

No. 12AAA217

- SJ-310/310R standard accessories
- Not available for the transverse tracing drive unit.



Nosepiece for cylindrical surfaces

No. 12AAA218


- SJ-310/310R standard accessories
- Not available for the transverse tracing drive unit.
- $\phi 30\text{mm}$ or smaller workpiece.



V-type adapter

No. 12AAE644


- SJ-310S standard accessories
- Dedicated to the transverse tracing drive unit.



Point-contact adapter


No. 12AAE643

- SJ-310S standard accessories
- Dedicated to the transverse tracing drive unit.



Extension rod (50 mm)

- Not available for the transverse tracing drive unit.



Extension cable (1 m)


No. 12BAA303

- For connecting calculation display unit and drive unit.

Support feet set

No. 12AAA216


- SJ-310 standard accessory
- Not attachable to the detector side of the transverse tracing drive unit.



Vertical positioning adapter


No. 12AAA219

- Not available for the transverse tracing drive unit




Magnetic stand adapter

- No. 12AAA221 ($\phi 8\text{mm}$)
- No. 12AAA220 ($\phi 9.5\text{mm}$)



Height gage adapter

- No. 12AAA222 (9x9mm)
- No. 12AAA233 (1/4inx1/2in)



Setting attachments

(Note: Not available for the transverse tracing drive unit)

Enhances measurement efficiency by facilitating the measurement setup of multiple workpieces of the same type and of the hard-to-access sections of a workpiece.

V-type for measuring axially

No. 178-033

The V-width is adjustable to the cylindrical workpiece diameter, facilitating axial measurement of a wide range workpiece sizes.

- Adjustable range: $\phi 5 \sim 150\text{mm}$



Slider type

No. 178-034

This attachment is ideal for measuring a flat area of a workpiece that has an indentation or step that makes it difficult to attach the drive unit. You can further improve the ease of use by using this attachment with the magnetic installation base (option: No. 12AAA910).



Inside diameter type

No. 178-035

Greatly facilitates measurement of internal wall surfaces of, for example, a cylinder block.

- Applicable diameter: $\phi 75 \sim \phi 95\text{mm}$
- Accessible depth: $30 \sim 135\text{mm}$



Optional Accessories: For External Equipment

Digimatic mini processor DP-1VR

By connecting this printer to the Surfptest SJ-310's digimatic output, you can print calculation results, perform a variety of statistical analyses, draw a histogram or D chart, and also perform complicated operations for X-R control charts.



No.264-504-5A

SJ-310→DP-1VR Connecting cable
1m: No.936937
2m: No.965014

Calculation results input unit INPUT TOOL

This unit allows you to load Surfptest SJ-310 calculation results (SPC output) into commercial spreadsheet software on a PC via a USB connector. You can essentially use a one-touch operation to enter the calculation results (values) into the cells in the spreadsheet software.



USB Input Tool Direct
USB-ITN-D
No.06ADV380D



USB keyboard signal conversion type*
IT-012U
No.264-012-10

*Requires the optional Surfptest SJ-310 connection cable.
1m: No.936937
2m: No.965014

Footswitch

A footswitch is used to trigger measurement. This tool is very useful in cases where you need to measure the same workpiece multiple times using jigs and other fixtures.



No.12AAJ088

Measurement Data Wireless Communication System U-WAVE

This unit allows you to remotely load Surfptest SJ-310 calculation results (SPC output) into commercial spreadsheet software on a PC.

You can essentially use a one-touch operation to enter the calculation results (values) into the cells in the spreadsheet software.



U-WAVE-R
(Connects to the PC)
No.02AZD810D



U-WAVE-T*
(Connects to the SJ-310)
No.02AZD880D

*Requires the optional Surfptest SJ-310 connection cable.
No.02AZD790D

Optional accessories and consumables for SJ-310

- Printer paper (5 rolls) **No.270732**
- Durable printer paper (5 rolls) **No.12AAA876**
- Touch-screen protector sheet (10 sheets) **No.12AAN040**
- Memory card (2GB) * **No.12AAL069**
- Connecting cable (for RS-232C) **No.12AAA882**

*micro SD card (with a conversion adapter to SD card)



- Coordinate Measuring Machines
- Vision Measuring Systems
- Form Measurement
- Optical Measuring
- Sensor Systems
- Test Equipment and Seismometers
- Digital Scale and DRO Systems
- Small Tool Instruments and Data Management

Note: All information regarding our products, and in particular the illustrations, drawings, dimensional and performance data contained in this printed matter as well as other technical data are to be regarded as approximate average values. We therefore reserve the right to make changes to the corresponding designs. The stated standards, similar technical regulations, descriptions and illustrations of the products were valid at the time of printing. In addition, the latest applicable version of our General Trading Conditions will apply. Only quotations submitted by ourselves may be regarded as definitive.

Mitutoyo products are subject to US Export Administration Regulations (EAR). Re-export or relocation of our products may require prior approval by an appropriate governing authority.

Trademarks and Registrations

Designations used by companies to distinguish their products are often claimed as trademarks. In all instances where Mitutoyo America Corporation is aware of a claim, the product names appear in initial capital or all capital letters. The appropriate companies should be contacted for more complete trademark and registration information.

Mitutoyo America Corporation
www.mitutoyo.com
 One Number to Serve You Better
1-888-MITUTOYO (1-888-648-8869)

- M³ Solution Centers**
Aurora, Illinois
 (Corporate Headquarters)
Westford, Massachusetts
Huntersville, North Carolina
Mason, Ohio
Plymouth, Michigan
City of Industry, California
Birmingham, Alabama
Renton, Washington

