

Material Safety Data Sheet

24 Hour Assistance:
1-847-367-7700

Rust-Oleum Corp.
www.rustoleum.com

1. Identification

Product Name: AUTORF 1-GL 2PK 1500 RUST INHIBITVE PRMR
Revision Date: 3/7/2013
Identification Number: 1573402
Product Use/Class: Primer/Alkyd
Supplier: Rust-Oleum Consumer Brands Canada (RCBC)
 200 Confederation Parkway
 Concord, ON L4K 4T8
 Canada
Manufacturer: Rust-Oleum Consumer Brands Canada (RCBC)
 200 Confederation Parkway
 Concord, ON L4K 4T8
 Canada
Preparer: Regulatory Department

2. Hazard Identification

EMERGENCY OVERVIEW: Harmful if swallowed. Causes eye irritation. Flammable liquid and vapor. Causes nose and throat irritation. Harmful If Inhaled. May affect the brain or nervous system causing dizziness, headache or nausea. Vapor Harmful. Causes Eye, Skin, Nose, and Throat Irritation.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Prolonged or repeated skin contact may cause irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. May cause headaches and dizziness. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

3. Composition/Information On Ingredients

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Talc	14807-96-6	30.0	2 mg/m3	N.E.	0.1 mg/m3 [Respirable]	N.E.
Xylene	1330-20-7	20.0	100 ppm	150 ppm	100 ppm	N.E.
n-Butyl Acetate	123-86-4	15.0	150 ppm	200 ppm	150 ppm	N.E.
Yellow Iron Oxide	51274-00-1	10.0	5 mg/m3	N.E.	10 mg/m3	N.E.
Ethylbenzene	100-41-4	5.0	20 ppm	125 ppm	100 ppm	N.E.
Barium Sulfate	7727-43-7	5.0	10 mg/m3	N.E.	15 mg/m3	N.E.
Zinc Phosphate	7779-90-0	5.0	N.E.	N.E.	N.E.	N.E.
Solvent Naptha, Light Aromatic	64742-95-6	5.0	N.E.	N.E.	N.E.	N.E.
1,2,4-Trimethylbenzene	95-63-6	5.0	25 ppm	N.E.	N.E.	N.E.

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

5. Fire-fighting Measures

Flash Point, °F 82 (Setaflash)

Extinguishing Media: Alcohol Foam, Carbon Dioxide, Dry Chemical, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Isolate from heat, electrical equipment, sparks and open flame.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Eliminate all ignition sources; use explosion-proof equipment. Place material in a container and dispose of according to local, provincial, state and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking.

9. Physical and Chemical Properties

Vapor Density	Heavier than Air	Odor:	Solvent Like
Appearance:	Liquid	Evaporation Rate:	Slower than Ether
Solubility in Water:	None	Freeze Point:	N.D.
Specific Gravity:	1.323	pH:	N.A.
Physical State:	Liquid		

(See section 16 for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

<u>Chemical Name</u>	<u>LD50</u>	<u>LC50</u>
Talc	N.E.	TCLo: 11 mg/m3 (Inhalation)
Xylene	4300 mg/kg (Rat, Oral)	5000 ppm (Rat, Inhalation, 4Hr)
n-Butyl Acetate	13100 mg/kg (Rat, Oral)	2000 ppm (Rat, Inhalation, 4 Hr)
Yellow Iron Oxide	>5000 mg/kg (Rat, Oral)	N.E.
Ethylbenzene	3500 mg/kg (Rat, Oral)	N.E.
Barium Sulfate	N.E.	N.E.
Zinc Phosphate	N.E.	N.E.
Solvent Naptha, Light Aromatic	4700 mg/kg (Rat, Oral)	3670 mg/kg (Rat, Inhalation)
1,2,4-Trimethylbenzene	N.E.	18000 mg/m3 (Rat, 4Hr)

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter waterways, wastewater. soil, storm drains or sewer systems.

14. Transport Information

	Domestic (USDOT)	International (IMDG)	Air (IATA)
Proper Shipping Name:	Consumer Commodity	Paint Related Material	Paint Related Material
Hazard Class:	ORM-D	3	3
UN Number:	N.A.	UN1263	UN1263
Packing Group:	N.A.	III	III
Limited Quantity:	No	Yes	Yes

15. Regulatory Information**U.S. Federal Regulations:****CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylene	1330-20-7
Ethylbenzene	100-41-4
Zinc Phosphate	7779-90-0
1,2,4-Trimethylbenzene	95-63-6

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

International Regulations:**CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS Class: B2 D2A D2B

16. Other Information**HMIS Ratings:**

Health: 2* **Flammability:** 3 **Physical Hazard:** 0 **Personal Protection:** X

NFPA Ratings:

Health: 2 **Flammability:** 3 **Instability:** 0

Volatile Organic Compounds, g/L: 503

REASON FOR REVISION: Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Consumer Brands Canada believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Consumer Brands Canada makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.