## **TECHNICAL DATA**

# **HRUST-OLEUM**

## **HEAVY DUTY BRAKE CLEANER**

## **DESCRIPTION AND USES**

Rust-Oleum<sup>®</sup> Heavy Duty Brake Cleaner use special nonchlorinated solvent power to remove contaminants from brake linings, drums, pads, cylinders and springs to ensure proper braking function. This low VOC product is compliant nationwide. It is suitable for use on brakes, clutches and engine components.

#### For Professional Use Only.

## FEATURES

- Dries quickly and leaves no residue
- Nationwide compliant VOC formula
- Removes heavy oil and grease residue

### PRODUCTS

| SKU    | Description                              |
|--------|--|
| 273920 | 14 oz. fill weight aerosol               |
| 274829 | 14 oz. fill weight aerosol (Canada only) |

## **PRODUCT APPLICATION**

#### APPLICATION

Use in a well ventilated area when temperatures are between  $50-90^{\circ}F$  (10-32°C). Avoid spraying in very windy and dusty conditions.

Shake well before and during use. Hold can 10-16" from the surface and spray in a steady back-and-forth motion. Spray brake parts liberally and allow to run off. Allow to air dry or use a soft wipe to clean the surface. Repeat as necessary. Protect rubber and plastic parts. Do not spray on warm or hot surfaces.

#### PRECAUTION

Vapors may ignite explosively. Keep away from heat, sparks and flame. Extinguish all flames and pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening all windows and doors to achieve cross ventilation. Avoid contact with eyes and skin.

### **CLEAN UP**

Properly dispose of container and unused contents in accordance with local, state and federal regulations.

#### STORAGE

Store in cool dry areas and protect from excessive heat.

## PHYSICAL PROPERTIES

| Physical Properties | HEAVY DUTY BRAKE CLEANER                      |
|---------------------|---|
| Solvent             | Acetone, Ethylbenzene, Methyl Acetate, Xylene |
| Fill Weight         | 14 ounces                                     |
| Shelf Life          | 5 years                                       |
| Flash Point         | -4°F (-20°C)                                  |
| Safety Information  | For additional information, see SDS           |

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com/industrial