



ALL PURPOSE

3006™ ORIGINAL FORMULA

Siliconized Acrylic Latex Caulk



White Lightning® 3006™ Original Formula is a siliconized acrylic latex all purpose caulk that features excellent adhesion to most surfaces, including wood, drywall, glass, masonry, brick, concrete and metal. It is ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents.

- Smooth Application
- Excellent Adhesion to Most Surfaces
- Cured Sealant is Mold and Mildew Resistant



PAINTABLE



INTERIOR/
EXTERIOR



WATER
CLEANUP

PART #	UPC	Color	SIZE
W12000010	0-23275-30060-6	White	10 fl oz
W12000005	0-23275-30066-8	White	5.5 fl oz
W12001010	0-23275-30067-5	Clear	10 fl oz
W12001005	0-23275-31067-4	Clear	5.5 fl oz
W12002010	0-23275-01010-9	Almond	10 fl oz
W12004010	0-23275-00610-2	Gray	10 fl oz
W12003010	0-23275-00810-6	Brown	10 fl oz

CLEAR



ALL PURPOSE

3006™
ORIGINAL
FORMULA

Smooth
Application

- Excellent Adhesion to Most Surfaces
- Cured Caulk is Mold and Mildew Resistant

SILICONIZED
ACRYLIC
LATEX CAULK



PAINTABLE



INTERIOR/
EXTERIOR



WATER CLEANUP



Exceeds
ASTM C-834

Product Description:

White Lightning® 3006™ Original Formula is a siliconized acrylic latex all purpose caulk that features excellent adhesion to most surfaces, including wood, drywall, glass, masonry, brick, concrete and metal. It is ideal for filling joints and openings around doors, windows, baseboards, trim, siding and vents.

Physical Properties:

Type: 100% Pure Acrylic With Silicone

Colors: White, Clear, Almond, Gray, Brown

Shelf Life: 24 Months

Flash Point: n/a (water based)

Flammability: n/a (water based)

Full Cure Time: 5 to 7 days at 75° F

Tack Free Time: 12 Minutes at 75° F

Application Temperature: above 40° F

Service Temperature: -30° F to 180° F

Vehicle: Water

Solids by Weight: 81.5% +/- .2%

Weight/Gallon: 13.20 +/- 0.2 lbs/gal

Painting: Paintable

Primers: Not required

Mildew Resistance: Good

Water Resistance: Good

Odor: Low

Shrinkage: Low/Moderate

Performance Data:

Joint Size: 1/8" x 1/8" to 1/2" x 1/4"

Freeze-Thaw Stability: Passes Through 5 Cycles

Shelf Life: 24 Months

Clean Up: Water, promptly clean tools and excess caulk with water or a damp cloth.

Flexibility: Very Good

Linear Coverage 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead ; 5.5oz squeeze tube 12ft at 1/4" wide by 1/4" deep bead

Painting: A minimum of 2-4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

NOTE: Acrylic Clear will apply appearing milky white and dry clear when fully cured.

ASTM: Exceeds ASTM Specification C-834 Tested at Riverbank Acoustical laboratories in accordance with ASTM E90 and C-919, this product was sound tested and proven to be an integral component in maintaining STC/MTC partition ratings. It has also been tested in accordance with ASTM C-Stet and D-217.

Application:

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

• 10oz cartridge

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

• 5.5oz cartridge

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

Clean Up:

Water; promptly clean tools and excess caulk with water or a damp cloth.

Cautions:

See MSDS

Limitations:

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

LIMITED WARRANTY:

LIMITED WARRANTY: LIMITED WARRANTY: For 40 years from date of purchase, if when applied according to label directions within one year from date of purchase, if this product fails to perform in accordance with the specifications set forth on this label, as your sole remedy, upon proof of purchase, we will replace the product at no cost or refund the original purchase price. Labor or costs associated with labor not included. Applies to single family house only. This warranty is made to the original residential consumer purchaser and is not transferable. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

For more information please call or write:

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com