

1" DRIVE IMPACT EXTENSIONS AND ACCESSORIES

Black Industrial Finish										
	Length	Use	Use	Socket						
Description	(Inches)	RET RING®	O-Ring / Pin	Retention						
Impact Extension	7	7-2XS	7-1B / 7-2D	Through Hole and Pin						
Impact Extension	13	7-2XS	7-1B / 7-2D	Through Hole and Pin						
Impact Universal Joint	4 1/2	7-3XS	7-1B / 7-2D	Through Hole and Pin						
3/4"M X 1"F Adapter	3	7-2XS	7-1B / 7-2D	Through Hole and Pin						
1-1/2"M X 1"F Adapter	3 3/8	7-2XS	7-1B / 7-2D	Through Hole and Pin						
	Description Impact Extension Impact Extension Impact Universal Joint 3/4"M X 1"F Adapter	Description Length (Inches)	Description Length (Inches) Use RET RING® Impact Extension Impact Extension Impact Extension Impact Universal Joint 3/4"M X 1"F Adapter 13 7-2XS 3/4"M X 1"F Adapter 3 7-2XS	Description Length (Inches) Use RET RING® Use O-Ring / Pin Impact Extension Impact Extension Impact Extension Impact Extension Impact Universal Joint 3/4"M X 1"F Adapter 13 7-2XS 7-1B / 7-2D 3/4"M X 1"F Adapter 3 7-2XS 7-1B / 7-2D						

Fed. Spec: ANSI B107.2

Features

- Specially heat treated for impact use to provide long life, safety, and durability
 Pin and o-ring or RET RING[®] (sold separately) secure tools onto impact wrench for safety and convenience
- Universal joint provides 55° range of motion Suitable for use with pneumatic and electric impact wrenches
- . Drive end features pin retention hole and groove



1" DRIVE IMPACT RETAINING PINS AND RINGS

Black Industrial Finish Product Code Description Application Diameter Length 7-1B Impact Retaining O-Ring NA Fits Williams Impact Tools with "B" Dimension to 2 3/8" 7-2D Impact Retaining Pin Fits Williams Impact Tools with "B" Dimension to 2 3/8" Impact Retaining Ŏ-Ring 7-1C 3 1/4 Fits Williams Impact Tools with "B" Dimension of 3 1/4" Impact Retaining Pin 7-2F 3/16 Fits Williams Impact Tools with "B" Dimension of 3 1/4"

Features

- . Specially heat treated for impact use to provide long life, safety, and durability.
- · Suitable for use with pneumatic and electric impact wrenches.
- For 1" Drive impact tools with pin retention hole and groove.







39006

39003

39004

39005



1" DRIVE RET RING® ONE-PIECE **IMPACT RETAINING RINGS WITH CRUSH GAUGE**

Product Code	Groove Diameter (Inches)	Application			
7-1XS	1 3/4	Fits Competitive Impact Sockets			
7-2XS	2	Fits Williams 1" Drive Tools with "B" Dimension of 2 1/8" and 2 1/4"			
7-3XS	2 1/8	Fits Williams 1" Drive Tools with "B" Dimension of 2 3/8"			
7-4XS	2 1/4	Fits Competitive Impact Sockets			
7-5XS	2 1/2	Fits Competitive Impact Sockets			
7-6XS	2 5/8	Fits Competitive Impact Sockets			

Features

- Fits all Williams 1" Drive Sockets and Accessories
- Crush Gage on the resin pin indicates when a socket is excessively worn and should be replaced.
- · Securely retains sockets and accessories to square drive of impact wrench
- . For 1" drive impact tools with pin retention hole and groove
- · Made of oil resistant material
- RET RING[®] is a trademark of FTL Enterprises, Inc.







1" DRIVE BUDD® WHEEL IMPACT SOCKET, 6 POINT, SAE

Black Industrial Finish											
		Α	В	С	D	E					
Product	Size	OAL	Drive End	Working End	Broach Depth	Bolt Clearance	Bolt Clearance				
Code	(Inches)	(Inches)	Diameter (Inches)	Diameter (Inches)	(Inches)	Depth (Inches)	Diameter (Inches)				
17-648BW	13/16 Square / 1 1/2 Hex	4	1 3/4	2 1/4	1 7/16	2 1/4	1 1/4				

Fed. Spec: ANSI B107.2 **Features**

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- 13/16" square opening threads stud into wheel.
- 1-1/2" hex opening engages and tightens the wheel lug nut.
- · Suitable for use with pneumatic and electric impact wrenches.
- Specially heat treated for impact use to provide long life, safety, and durability.



17-648BW





